according to Regulation (EC) No. 1907/2006

# Sika® Bonding Primer (A)

Revision Date 01.10.2014 Version 1.0



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Sika® Bonding Primer (A)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

### 1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Telephone : +44 (0)1707 394444

### 1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Type of product : Mixture

### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

### Classification (67/548/EEC, 1999/45/EC)

Not a hazardous substance or mixture.

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

# Additional Labelling:

Safety data sheet available on request.

### 2.3 Other hazards

Revision Date 01.10.2014

according to Regulation (EC) No. 1907/2006

# Sika® Bonding Primer (A)





This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

### **Hazardous components**

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]		
benzyl alcohol 100-51-6 202-859-9 01-2119492630-38-XXXX	Xn; R20/22	Acute Tox.4; H302 Acute Tox.4; H332 Eye Irrit.2; H319	>= 1 - < 2,5		
Substances with a workplace exposure limit :					
1-methoxy-2-propanol 107-98-2 203-539-1 01-2119457435-35-XXXX	R10 R67	Flam. Liq.3; H226 STOT SE3; H336	>= 2,5 - < 5		

For the full text of the R-phrases mentioned in this Section, see Section 16. For the full text of the H-Statements mentioned in this Section, see Section 16.

# **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : See Section 11 for more detailed information on health effects

and symptoms.

Risks : No known significant effects or hazards.

### 4.3 Indication of any immediate medical attention and special treatment needed

according to Regulation (EC) No. 1907/2006

# Sika® Bonding Primer (A)

Revision Date 01.10.2014 Version 1.0 Print Date 01

**Treatment** : Treat symptomatically.

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

### 5.2 Special hazards arising from the substance or mixture

### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

# 6.2 Environmental precautions

**Environmental precautions** : No special environmental precautions required.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8. No special handling

advice required. Follow standard hygiene measures when

handling chemical products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

# 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

according to Regulation (EC) No. 1907/2006

# Sika® Bonding Primer (A)

Revision Date 01.10.2014 Version 1.0 Print Date 01.10.2014

Advice on common storage : No special restrictions on storage with other products.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Components with workplace control parameters

Components	CAS-No.	Value	Control parame-	Basis *
			ters *	
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC
		STEL	150 ppm 568 mg/m3	2000/39/EC
		TWA	100 ppm 375 mg/m3	GB EH40
		STEL	150 ppm 560 mg/m3	GB EH40

# 8.2 Exposure controls

### Personal protective equipment

Eye protection : Safety glasses

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Butyl rubber/nitrile rubber gloves (0,4 mm), Recommended: Butyl rubber/nitrile rubber gloves.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

according to Regulation (EC) No. 1907/2006

# Sika® Bonding Primer (A)

Revision Date 01.10.2014 Version 1.0



organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### **Environmental exposure controls**

General advice : No special environmental precautions required.

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : white

Odour : very faint

Odour Threshold : No data available

Flash point : Note: not applicable

> 100 °C

Ignition temperature : not applicable

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

Auto-ignition temperature : No data available

pH : ca. 9,5

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Vapour pressure : No data available

Density : ca.1 g/cm3

at 20 °C

according to Regulation (EC) No. 1907/2006

# Sika® Bonding Primer (A)

Revision Date 01.10.2014 Version 1.0

Print Date 01 10 2014

Water solubility : Note: soluble

Partition coefficient: n-

Viscosity, dynamic

: No data available

octanol/water

: No data available

Viscosity, kinematic : 7 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

### 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

# 10.6 Hazardous decomposition products

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

### Acute toxicity

# **Components:**

benzyl alcohol:

Acute oral toxicity : LD50 Oral rat: 1.230 mg/kg

Acute inhalation toxicity : LC50 rat: 4,178 mg/l

Exposure time: 4 h

according to Regulation (EC) No. 1907/2006

# Sika® Bonding Primer (A)

Revision Date 01.10.2014 Version 1.0



Test atmosphere: dust/mist

1-methoxy-2-propanol:

Acute oral toxicity : LD50 Oral rat: > 5.000 mg/kg

Acute inhalation toxicity : LC50 : 7,5 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal rabbit: > 5.000 mg/kg

Skin corrosion/irritation

**Product** 

No data available

Serious eye damage/eye irritation

**Product** 

No data available

Respiratory or skin sensitisation

**Product** 

No data available

Germ cell mutagenicity

**Product** 

Mutagenicity : No data available

Carcinogenicity

**Product** 

Carcinogenicity : No data available

Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

No data available

Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

No data available

STOT - single exposure

No data available

STOT - repeated exposure

according to Regulation (EC) No. 1907/2006

# Sika® Bonding Primer (A)

Revision Date 01.10.2014 Version 1.0



No data available

# **Aspiration toxicity**

No data available

### **SECTION 12: Ecological information**

# 12.1 Toxicity

### **Components:**

# 1-methoxy-2-propanol:

Toxicity to fish : LC50: > 100 mg/l, 96 h, Fish

Toxicity to daphnia and other : EC50: > 100 mg/l, 48 h, Daphnia

aquatic invertebrates

# 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

# 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

### 12.6 Other adverse effects

No data available

# **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

**Product** : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental

according to Regulation (EC) No. 1907/2006

# Sika® Bonding Primer (A)





protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 12 waste paint and varnish other than those mentioned

in 08 01 11

# **SECTION 14: Transport information**

**ADR** 

Not dangerous goods

**IATA** 

Not dangerous goods

**IMDG** 

Not dangerous goods

# 14.6 Special precautions for user

No data available

# 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Special labelling of certain

mixtures

: Safety data sheet available for professional user on request.

REACH Information: All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

VOC-CH (VOCV) : 2,5 %

no VOC duties

VOC-EU (solvent) : 4,8 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or : The Chemicals (Hazard Information and Packaging for Sup-

ply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

mixture:

according to Regulation (EC) No. 1907/2006

# Sika® Bonding Primer (A)

Revision Date 01.10.2014 Version 1.0



1999

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

### **SECTION 16: Other information**

#### Full text of R-Phrases

R10 Flammable.

R20/22 Harmful by inhalation and if swallowed.

R67 Vapours may cause drowsiness and dizziness.

#### **Full text of H-Statements**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

### Full text of other abbreviations

Acute Tox. Acute toxicity
Eye Irrit. Eye irritation
Flam. Liq. Flammable liquids

STOT SE Specific target organ toxicity - single exposure

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.

Changes as compared to previous version!