

PRODUCT DATA SHEET

Sika® Trocal Cleaner L-100

Sikaplan Cleaner

PRODUCT DESCRIPTION

Sika® Trocal Cleaner L-100 is a solvented cleaner for preparing Sikaplan® roof waterproofing membranes

USES

- Cleaner to remove local contamination from Sikaplan® roof waterproofing and waterproofing membrane seams
- Preparation of old Sikaplan® PVC membranes for welding applications
- Diluent for Sika-Trocal® C 733 adhesive
- Degreasing metal sheets
- Preparation of PVC membranes for solvent welding

CHARACTERISTICS / ADVANTAGES

- Dissolves contamination from adhesive resin, mastic and bitumen
- Evaporates quickly
- Highly flammable
- The cleaner may be suitable to clean metal equipment and tools

PRODUCT INFORMATION

Chemical Base	Mixture of high volatile solvents	
Packaging	Container:	4 kg, 9 kg
	Packing unit:	Euro pallet or single container
Refer to current price list for packaging variations.		
Appearance / Colour	Transparent	
Shelf Life	24 months from date of production	
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions and protected from direct sunshine. The product is highly flammable: Safety regulations regarding storage and handling of dangerous goods must be observed. Always refer to packaging.	
Density	0,9 kg/l	
Consistency	Liquid	

APPLICATION INFORMATION

Ambient Air Temperature	+30 °C min. / +60 °C max.
Substrate Temperature	-20 °C min. / +60 °C max.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTS

- Installation instructions: Relevant roof waterproofing membrane.

LIMITATIONS

- Dissolves thermoplastics not resistant to solvents (e.g. polystyrene, polycarbonate, acrylics)
- Do not use the cleaner to wash large areas of roof surface.
- Sika® Trocal Cleaner L-100 reduces the seam quality and must only be used on heavily soiled areas.
- Use solvent resistant gloves and eye protection glasses during application.
- The least amount of cleaner degrades thermoplastic surfaces.
- Sika® Trocal Cleaner L-100 contains high volatile and flammable solvents. Application in closed rooms must only be carried out with sufficient room ventilation. Do not smoke and avoid open flames.
- Product residue will evaporate rapidly.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

APPLICATION

Reference must be made to further documentation where applicable, such as relevant method statement, application manual and installation or working instructions.

Application as cleaner

Sika® Trocal Cleaner L-100 has high deteriorating effect on textile colours and dirt. In order to prevent discolorations on the membrane surface, it is recommended to use white cleaning cloths. Spilt Sika® Trocal Cleaner L-100 must be soaked up with dry cloths immediately. Cleaner on the membrane surface must be fully evaporated prior to seam welding.

Application as adhesive diluent

Refer to Sika-Trocal® C 733 Product Data Sheet

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal

conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

TECHNICAL ENQUIRIES

Tel: 01707 358500
Web: www.sikatrococal.co.uk
Twitter: @SikaTrococal

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



EMS 45308



OHS 585274

Product Data Sheet

Sika® Trocal Cleaner L-100
March 2025, Version 01.02
020945071050000002

SikaTrocalCleanerL-100-en-GBTROCAL-(03-2025)-1-2.pdf