

PRODUCT DATA SHEET

SikaShield® Roof GRP Edge Trims

GRP ROOF EDGE TRIMS FOR USE WITH BITUMINOUS MEMBRANES

PRODUCT DESCRIPTION

A range of GRP (Glass reinforced plastic) roof edge trims used to terminate SikaShield® bituminous membrane systems.

USES

The SikaShield® Roof GRP Edge Trims are a range of check trims for the termination of SikaShield® membranes

CHARACTERISTICS / ADVANTAGES

- Will not corrode, rust or dent
- Negligible coefficient of expansion
- Preformed corners available
- UV protected

PRODUCT INFORMATION

Packaging	SikaShield® Roof GRP Edge Trims Type W, X Y and Z are supplied in 3m lengths. Internal/External corners are available to match, each sold separately.	
Shelf Life	N/A	
Storage Conditions	Store in dry conditions.	
Dimensions	Type W	40mm/60mm (face depth/overall width)
	Type X	65mm/60mm (face depth/overall width)
	Type Y	100mm/60mm (face depth/overall width)
	Type Z	150mm/60mm (face depth/overall width)

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Choose the appropriate profile for site conditions and screw fix using stainless steel screws. Butt plates are to be inserted at all joints and preformed corner units are to be used where appropriate. SikaShield® Roof GRP Edge Trims Type W, X, and Y must be fixed at a maximum 300mm staggered centres. SikaShield® Roof GRP Edge Trims Type Z must be fixed at a maximum 150mm staggered centres. The appropriate Sika Ltd mechanical fasteners must be used in these scenarios, and depends upon the substrate that is being fixed into. Pre-formed corners are to be fixed with a minimum of two staggered fixings per leg. Note: For advice regarding waterproofing into the trim please refer to the SikaShield® specification and detail drawings.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
SikaShield® Roof GRP Edge Trims
December 2022, Version 01.01
02094513900000090

SikaShieldRoofGRPEdgeTrims-en-GB-(12-2022)-1-1.pdf