

PRODUCT DATA SHEET

Cromar® Contractor G 25 Top Coat

Contractors grade GRP liquid roofing top coat.

PRODUCT DESCRIPTION

Cromar® Contractor G 25 GRP is a professional roofing system designed for durable, high performance flat roofing applications. It comprises a Contractor G 25 Resin and a Contractor G 25 Topcoat, both engineered to deliver strong mechanical performance, reliable curing, and long-term weather resistance.

USES

Designed for use with Cromar® Contractors G 25 Resin to provide a durable, watertight, weather resistant finish.

CHARACTERISTICS / ADVANTAGES

- Cures to a tack-free, watertight coating.
- Excellent water and weather resistance.

PRODUCT INFORMATION

Packaging	Labelled tins available in 10 kg & 20 kg.
Colour	Grey
Shelf Life	6 months.
Storage Conditions	Cromar® Contractor G 25 Top Coat should be stored indoors between + 5 °C to + 20 °C away from sources of ignition and naked flames etc. Store away from children.
Flash Point	+32 °C
Viscosity	With spindle 4 and 60 rpm: 6500 - 7500 cps
Curing Time	11 - 16 minutes.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

USES

Cromar® Contractor G 25 Top Coat is not recommended for use in conditions under +5 °C.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

Topcoat Application:

- Mix Cromar® Contractor G 25 Top Coat with the appropriate MEKP catalyst (the PRO GRP Hardener is compatible for use) to achieve correct curing.
- Apply once the laminate (resin base coat) has fully cured (typically 1–2 hours).
- Apply evenly to achieve 0.5 to 0.6 mm wet film thickness for correct performance.
- Ensure surface is completely dry and dust-free before coating.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® Contractor G 25 Top Coat
April 2026, Version 01.03
020915953000247791

CromarContractorG25TopCoat-en-GB-(04-2026)-1-3.pdf