

Everbuild 705 Rapid Set Tile Adhesive

DECLARATION OF PERFORMANCE

No. 86830711

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	RAPID
2	INTENDED USE/S	Fast setting cementitious tile adhesive with reduced slip
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate Leeds, LS9 0SW
4	AUTHORISED REPRESENTATIVE:	Not Applicable
5	SYSTEM/S OF AVCP:	3
6a	HARMONISED STANDARD:	EN12004:2007
	Notified body/ies:	1289

Declaration of Performance

RAPID

86830711

2021/1, ver. 01

1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reduced Slip	≤ 0.5 mm		EN12004: 2007
Reaction to fire	Class E		
Bond Strength as:			
Early tensile adhesion strength	≥ 0.5 N/mm ²		
Initial Adhesion strength	≥ 0.5 N/mm ²		
Open time tensile adhesion	≥ 0.5 N/mm ²		
Durability of bond strength against climate / heat aging action	≥ 0.5 N/mm ²		
Durability of bond strength against water / humidity aging action	≥ 0.5 N/mm ²		
Durability of bond strength against freeze thaw cycles	≥ 0.5 N/mm ²		
Release of dangerous substances	see sds		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product
Coordinator
At Leeds on 19 January 2021

Name : Mariam Maqsood
Function: Product Manager
At Leeds on 19 January 2021



End of information as required by UKCA

Declaration of Performance

RAPID
86830711
2021/1, ver. 01
1213



21

Everbuild Building Products LTD, Leeds, UK

DoP No. 86830711

EN12004:2007

Notified Body 1289

Fast setting cementitious tile adhesive with reduced slip

Reduced Slip	≤ 0.5 mm
Reaction to fire	Class E
Bond Strength as:	
Early tensile adhesion strength	≥ 0.5 N/mm ²
Initial Adhesion strength	≥ 0.5 N/mm ²
Open time tensile adhesion	≥ 0.5 N/mm ²
Durability of bond strength against climate / heat aging action	≥ 0.5 N/mm ²
Durability of bond strength against water / humidity aging action	≥ 0.5 N/mm ²
Durability of bond strength against freeze thaw cycles	≥ 0.5 N/mm ²
Release of dangerous substances	see sds

For DOP see www.everbuild.co.uk/downloads/**ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

RAPID
86830711
2021/1, ver. 01
1213

Declaration of Performance

RAPID

86830711

2021/1, ver. 01

1213

