

PRODUCT DATA SHEET

Sikafloor®-02 Primer

ACRYLATE FLOORING PRIMER FOR LEVELLING COMPOUNDS AND TILE ADHESIVES



PRODUCT DESCRIPTION

Sikafloor®-02 Primer is a 1-part, acrylate resin for priming non-absorbent substrates before applying cementitious levelling compounds and tile adhesives.

USES

As a primer for:

- Improving adhesion on smooth and sound non-absorbent substrates
- Interior use only

CHARACTERISTICS / ADVANTAGES

- 1-part
- Provides optimum adhesion on non-absorbent substrates
- Low consumption / high coverage
- Suitable for use with underfloor heating
- Short waiting times
- Very low emissions
- Easy to apply by roller
- Ready for use
- Solvent-free according to TRGS 610

ENVIRONMENTAL INFORMATION

- IBU Environmental Product Declaration (EPD)
- VOC emission classification GEV-Emicode EC1^{PLUS}, license number 6159/24.02.97

PRODUCT INFORMATION

Chemical Base	Special acrylate dispersion with additives.
Packaging	5 and 12 kg containers Refer to current price list for packaging variations
Appearance / Colour	Blue liquid
Shelf Life	12 months from date of production
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.
Density	1.3 kg/l

APPLICATION INFORMATION

Substrates	Non-absorbent substrate compatibility: <ul style="list-style-type: none">▪ Concrete▪ Cementitious screeds▪ Substrates with existing water-resistant adhesive residue▪ Ceramic tiles▪ Natural stones▪ Terrazzo (epoxy or cementitious)▪ Mineral based magnesia screeds▪ Metals▪ Epoxy and water-based polyurethane surfaces▪ Fully bonded resilient floorings (except polyolefin coverings)▪ Mastic asphalt screeds IC 10 and IC 15 according to EN 13 813▪ Other substrate types contact Sika Technical Services						
Consumption	~125 g/m ² This figure is theoretical and does not allow for any additional material due to surface porosity, surface profile, variations in level or wastage etc.						
Ambient Air Temperature	+5 °C min. / +30 °C max.						
Substrate Temperature	+5 °C min. / +30 °C max.						
Waiting Time / Overcoating	Levelling compounds and tile adhesives on Sikafloor®-02 Primer: <table border="1"><thead><tr><th>Substrate</th><th>Waiting Time</th></tr></thead><tbody><tr><td>Non-absorbent substrates as mentioned in substrate section excluding mineral based magnesia screeds</td><td>~1.5 hours</td></tr><tr><td>Mineral based magnesia screeds</td><td>~4 hours</td></tr></tbody></table> <p>Times are approximate and will be affected by changing ambient conditions particularly temperature and relative humidity. Reference must be made to the individual Product Data Sheets of the levelling compounds and tile adhesives.</p>	Substrate	Waiting Time	Non-absorbent substrates as mentioned in substrate section excluding mineral based magnesia screeds	~1.5 hours	Mineral based magnesia screeds	~4 hours
Substrate	Waiting Time						
Non-absorbent substrates as mentioned in substrate section excluding mineral based magnesia screeds	~1.5 hours						
Mineral based magnesia screeds	~4 hours						

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

General

The existing substrate must be sound, structurally stable, clean, dry and free of all contaminants such as dirt, oil, grease, wax and rust which could affect adhesion.

All dust, loose and friable material must be completely removed from all substrate types before the application of Sikafloor®-02 Primer, preferably by vacuum extraction equipment.

Suitable preparation techniques include: abrasive blast cleaning, grinding, abrading, electric floor scrubbers used with de-greasing / cleaning chemicals.

Concrete / cementitious screeds

De-grease and clean

Water soluble adhesive residue

Completely remove

Water resistant adhesive residue

Mechanically remove as thoroughly as possible leaving only well bonded residue

Resilient floor coverings

These must be securely bonded to the substrate. Remove poorly bonded coverings. De-grease and clean.

Ceramic tiles, natural stones, terrazzo, epoxy and water-based polyurethane coatings

These must be securely bonded to the substrate. Abrade surfaces to remove glaze or gloss finish. Replace any tiles or stones that are loose before abrading.

Vinyl coverings containing asbestos

These must be securely bonded to the substrate. Remove poorly bonded coverings. De-grease and clean.

Metals

De-grease and clean. Mechanically remove rust.

Mineral based magnesia screeds

De-grease and clean

MIXING

Ready to use, Stir before use.

APPLICATION

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Apply primer onto the prepared substrate by short-pile roller or pad applicator. Ensure a continuous, pore free coat covers the substrate. Avoid the formation of puddles.

Confirm waiting /overcoating time has been achieved before applying subsequent products.

CLEANING OF TOOLS

Clean all tools and application equipment with water immediately after use. Hardened material can only be removed mechanically

LIMITATIONS

- If used on soft existing coverings i.e. vinyl, linoleum or rubber substrates, always use a gypsum based levelling compound.
- Magnesia screeds other than mineral based, e.g. wood flour magnesia, must be primed with an epoxy based primer and fully broadcast with kiln dried quartz sand before application of levelling compound and tile adhesive.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet
Sikafloor®-02 Primer
November 2019, Version 04.01
020815120010000043

Sikafloor-02Primer-en-GB-(11-2019)-4-1.pdf