

PRODUCT DATA SHEET

Cromar[®] Secret Jointing Strip

Plastic jointing strip between adjacent roofs.

PRODUCT DESCRIPTION

Cromar[®] Secret Jointing Strip is a durable, cost effective alternative to lead and zinc valleys.

USES

- Can be used on tile and slate roofs.
- Used to create a weatherproof seal between roofs or terraced houses, or where a new roof needs to join an existing one.

PRODUCT INFORMATION

Packaging	Boxed
Colour	Black
Shelf Life	Plastic items have not been assessed for shelf life due to their longevity
Storage Conditions	The product must be stored undamaged in packaging, in dry conditions at temperatures between +5 °C and +30 °C
Length	3000 mm
Width	216 mm

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of

CHARACTERISTICS / ADVANTAGES

- Light weight and easy to install.
- Long-lasting.
- Cost effective alternative to lead gutters.
- Virtually maintenance free.

the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

- Position the Secret Jointing Strip centrally over the

joint between adjacent tiles or slates.

- Ensure the lower end of the strip is correctly aligned to allow water to drain freely toward the eaves.
- Hook the bottom end securely over the top edge of the underlying tile to create a continuous drainage channel.
- Lay the tiles on each side so they overlap the strip evenly, ensuring the strip remains aligned.
- Fix adjacent tiles in accordance with the tile manufacturer's fixing schedule.
- Continue installing additional strips as required, ensuring each piece is seated properly and not forced out of alignment.
- Check that there are no gaps where wind-driven rain could penetrate at the tile interfaces.
- After installation of each course, visually inspect to ensure the strip remains central and free from distortion

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® Secret Jointing Strip
February 2026, Version 01.01
020945201000247190

CromarSecretJointingStrip-en-GB-(02-2026)-1-1.pdf