

# Sika MonoTop®-615

# **DECLARATION OF PERFORMANCE**

No. 43739898

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	43739898
2	INTENDED USE/S	EN 1504-3:2005 Structural and non-structural repair products for concrete for application in buildings and civil engineering work
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ for type testing System 3 for reaction to fire
6a	HARMONISED STANDARD:	EN 1504-3:2005
	Notified body/ies:	1029

#### 7 **DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Compression strength	≥ 25 Mpa	System 2+	EN 1504- 3:2005
Chloride ion content	≤ 0.05 %	System 2+	
Adhesive bond	≥ 1.5 MPa	System 2+	
Carbonation resistance	Pass	System 2+	
Elastic modulus	≥ 15 GPa	System 2+	
Thermal compatibility freeze-thaw	NPD	System 2+	
Skid resistance	NPD	System 2+	
Coefficient of thermal expansion	NPD	System 2+	
Capillary absorption	≤ 0.5 kg.m <sup>-2</sup> .h <sup>-0.5</sup>	System 2+	
Reaction to fire	Class A1	System 3	
Release of dangerous substances	NPD	System 2+	

#### 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Jamie Squires Function: Product Manager Engineered refurbishment

At Sika Ltd on 01 December 2020

Name: Martin Liska Function: R & D Manager

At Sika Ltd on 01 December 2020

End of information as required by Regulation (EU) No 305/2011





20

Sika Services AG, Zurich, Switzerland

DoP No. 43739898

EN 1504-3:2005

Notified Body 1029

Structural and non-structural repair products for concrete for application in buildings and civil engineering work

 Compression strength
 ≥ 25 Mpa

 Chloride ion content
  $\leq$  0.05 %

 Adhesive bond
  $\geq$  1.5 MPa

 Carbonation resistance
 Pass

Elastic modulus ≥ 15 GPa

Capillary absorption  $\leq 0.5 \text{ kg.m}^{-2}.\text{h}^{-0.5}$ 

Reaction to fire Class A1

http://dop.sika.com

### **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## **LEGAL NOTE**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland www.sika.com

**Declaration of Performance** 

Sika MonoTop®-615 43739898 2020.01, ver. 2 3202

