

PRODUCT DATA SHEET

SikaRoof® SF-RS-5.8

CARBON STEEL SELF-DRILLING FASTENER FOR SIKA-TROCAL ROOFING SYSTEMS

PRODUCT DESCRIPTION

The SikaRoof® SF-RS-5.8 high quality self-drilling fastener is manufactured from SAE1022 case hardened steel.

USES

Used with dedicated accessories for the attachment of Sika- Trocal® Roof waterproofing membrane.

CHARACTERISTICS / ADVANTAGES

- Optimised thread design for excellent pull-out performance and resistance to unwinding.
- Drillpoint designed for fast accurate penetration of metal decks up to 2 x 1mm and timber up to 25mm
- Versatile design for metal and timber substrates
- Compatible with the Sika-Trocal® range of tube washers and pressure plates
- Purpose designed and precision manufactured

PRODUCT INFORMATION

Chemical Base	SAE1022 case hardened steel with multiple layer organic coating. Low profile oval style, TX25 recess
Packaging	See current price list
Shelf Life	Will not expire under normal conditions
Storage Conditions	Must be stored between +5 °C and +30 °C in original packaging protected from direct sunlight, rain, snow and chemicals
Dimensions	Shaft diameter - 5.8mm Head diameter - 9.1mm Tube lengths - see current price list

APPLICATION

Fasteners should be driven with a variable speed electric screwdriver (at no more than 1500rpm) and TX25 drive bar, within three degrees of perpendicular to the surface of the fastened material. Avoid over-driving,

and do not over-tighten.

VALUE BASE

All technical data stated in this Product Data Sheet are

based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet

SikaRoof® SF-RS-5.8
November 2019, Version 01.01
020945051100000054

SikaRoofSF-RS-58-en-GB-(11-2019)-1-1.pdf