

Parex 100 Newton Grout

DECLARATION OF PERFORMANCE

No. 42577

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	42577
2	INTENDED USE/S	For uses in buildings and civil engineering works - Structural and non-structural repair products for concrete, used by applying mortar by hand, by recasting with concrete, by spraying concrete or mortar, by increasing cover to reinforcement with additional cementitious mortar or concrete and structural strengthening by adding mortar or concrete. For uses subject to reaction to fire regulations.
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
4	SYSTEM/S OF AVCP:	System 2+ System 3
5a	HARMONISED STANDARD:	EN 1504-3:2005
Notified body/ies:		1029

Declaration of Performance

Parex 100 Newton Grout

42577

2025.06, ver. 1

3202

6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Compressive strength	≥ 45 MPa	System 2+	EN 1504-3:2005
Chloride ion content	$\leq 0,05$ %	System 2+	
Adhesive bond	$\geq 2,0$ MPa	System 2+	
Carbonation resistance	Pass	System 2+	
Elastic modulus	≥ 20 GPa	System 2+	
Thermal compatibility	$\geq 2,0$ MPa	System 2+	
Capillary absorption	$\leq 0,5$ kg·m ⁻² ·h ^{-0,5}	System 2+	
Reaction to fire	Euroclass A1	System 3	

7 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Rob Doherty
Function: Head Of Product
Management
At Welwyn Garden City on 06 June
2025



Name: Martin Liska
Function: Head Of U.K. R&D
At Welwyn Garden City on 06 June 2025



End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of Performance

Parex 100 Newton Grout
42577
2025.06, ver. 1
3202



25

Sika Services AG, Zurich, Switzerland

42577

Compressive strength	≥ 45 MPa
Chloride ion content	≤ 0,05 %
Adhesive bond	≥ 2,0 MPa
Carbonation resistance	Pass
Elastic modulus	≥ 20 GPa
Thermal compatibility	≥ 2,0 MPa
Capillary absorption	≤ 0,5 kg·m ⁻² ·h ^{-0,5}
Reaction to fire	Euroclass A1

EN 1504-3:2005

1029

For uses in buildings and civil engineering works - Structural and non-structural repair products for concrete, used by applying mortar by hand, by recasting with concrete, by spraying concrete or mortar, by increasing cover to reinforcement with additional cementitious mortar or concrete and structural strengthening by adding mortar or concrete.

For uses subject to reaction to fire regulations.

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Parex 100 Newton Grout

42577

2025.06, ver. 1

3202

Sika Services AG
Tüffenwies 16
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance

Parex 100 Newton Grout
42577
2025.06, ver. 1
3202

