

PRODUCT DATA SHEET

Sika[®] Antisol[®]-10 GB

CURING AGENT

PRODUCT DESCRIPTION

Sika[®] Antisol[®]-10 GB is used in concrete construction for curing.

USES

- Concrete for traffic areas e.g. Roads, airfields
- For non-traffic components Screed
- At high temperatures, strong sunlight, wind movement as well as in low humidity

CHARACTERISTICS / ADVANTAGES

Sika[®] Antisol[®]-10 GB is a highly effective solvent-free wax emulsion and creates, a largely water vapour impermeable protective film on the concrete surface after drying.

- Blocking the surface pores of the concrete
- Extremely high evaporation protection
- Protection against dehydration
- Prevention against contraction and shrinkage cracks

APPROVALS / STANDARDS

Curing efficiency 101% according to TL NBM-StB 09.

PRODUCT INFORMATION

Chemical Base	Water-based, paraffin wax dispersion
Packaging	Canister: 10 kg
Shelf Life	Minimum of 6 months shelf life in sealed containers.
Storage Conditions	Protect against frost, strong sunlight and contamination.
Appearance / Colour	Fluid / White
Density	0.99 g/cm ³ at +20°C

APPLICATION INFORMATION

Recommended Dosage	150 g/m ² to 200 g/m ²
Ambient Air Temperature	> +1°C

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Sika® Antisol®-10 GB
June 2024, Version 01.01
021405031000000182

SikaAntisol-10GB-en-GB-(06-2024)-1-1.pdf