

PRODUCT DATA SHEET

Sika® Sprayguard

PROTECTION AGENT FOR CONCRETE MIXERS

PRODUCT DESCRIPTION

Sika® Sprayguard is a ready to use, blend of selected oils developed to protect concrete mixing equipment.

USES

Sika® Sprayguard can be applied on all mixing equipment that is in contact with fresh concrete and mortar. Sika® SprayGuard® is mainly used for the following applications:

- A wide range of applications where mixing equipment requires protection
- Forced action concrete and mortar mixes
- Truck mixers and drums

CHARACTERISTICS / ADVANTAGES

Sika® Sprayguard allows for an increased service life of all mixing and transportation equipment.

- Excellent “sticking” ability
- Reduces corrosive action of cement on metal surfaces
- Extended service life of equipment
- Easy to use

APPROVALS / STANDARDS

Sika Limited operates a Quality Management Systems ISO 9001

PRODUCT INFORMATION

Chemical Base	Mineral oil.
Packaging	20 litre drum, 200 litre drum
Appearance / Colour	Opaque Liquid
Shelf Life	12 months from date of production if stored properly in undamaged unopened, original sealed packaging.
Storage Conditions	Store in dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight and frost.
Density	0.89 Kg/Litre
Consumption	Sika® Sprayguard consumption is dependant on application circumstances.
Equipment	Clean all tools and application equipment with water immediately after use.

APPLICATION

We recommend the use of a special spray gun with an operating pressure of 3-6 bar and a flat spraying nozzle.

LIMITATIONS

Contact our Technical Service Department for information and advice about any specific combinations.

To maintain the protective action of Sika® Sprayguard, Sika® Sprayguard should be applied to surfaces regularly. Support from our Technical Service Department is recommended.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet
Sika® Sprayguard
December 2018, Version 02.01
021405021000000035

SikaSprayguard-en-GB-(12-2018)-2-1.pdf