

PRODUCT DATA SHEET

Cromar® Simulated Lead Flashing Trim

Lead flashing alternative

PRODUCT DESCRIPTION

Cromar® Simulated Lead Flashing Trim is a pre-formed lead simulation trim that is meant to be used as a replacement for lead flashing. Fitted as a flashing, it can be cut on site and made to measure and does not require a topcoat as it already has a waterproof coating. The flashing trim is inserted into a chase cut into the brick-work and bonded with a trim adhesive which eliminates the possibility of water ingress. The trim will slot into the brickwork itself, requiring a 25 mm chase to be cut between two brickwork courses for the return to set into.

USES

- As a replacement for lead flashing.
- Used as part of a PRO GRP and Flexiglass roofing systems.

CHARACTERISTICS / ADVANTAGES

- Simulated lead flashing.
- Preformed and prefinished.
- Designed to be used instead of lead flashing.
- For use as part of the PRO GRP and Flexiglass roofing systems.
- Supplied in 3 m lengths.

PRODUCT INFORMATION

Packaging	Boxed
Colour	Grey
Shelf Life	Physical plastic items have not had their shelf life determined due to longevity
Storage Conditions	The product must be stored properly in undamaged packaging, in dry conditions at temperatures between +5 °C and +30 °C.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no sub-

stances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the

European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

APPLICATION

Cut a chase into the brickwork mortar joint with a suitable angle grinder and insert the flashing trim into the chase after applying a continuous bead of trim adhesive to the rear side, this will bond the flashing trim to angle fillet preventing any possible water ingress. Press firmly into the chase, overlapping the angle fillet and point neatly with adhesive.

The trim will slot into the brickwork itself which means that you will need to cut a 25 mm chase between two brickwork courses for the return to set into.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED
Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® Simulated Lead Flashing Trim
February 2026, Version 01.01
020945119000247257

CromarSimulatedLeadFlashingTrim-en-GB-(02-2026)-1-1.pdf