

PRODUCT DATA SHEET

Leadax Original Flashing

Leadax Original - PVB lead free flashing

PRODUCT DESCRIPTION

Leadax Original produced from recycled polyvinyl butyral (PVB); the safety film in laminated glass such as car windows. Unlike traditional lead, it contains no heavy metals and has no negative effects on health or the environment (can be recycled).

USES

For sealing around dormers, windows, chimneys, abutments, valleys and ridges.

CHARACTERISTICS / ADVANTAGES

- Lightweight
- Malleable - similar to lead
- Strong

PRODUCT INFORMATION

Packaging	Individually wrapped in polythene sleeve with paper product label.		
Colour	Grey		
Shelf Life	25 years.		
Storage Conditions	Leadax Original should be stored in a ventilated area, away from frost, humidity and at temperatures - 5 to + 30 °C. However, prior to use, the product must acclimatise to minimum processing temperature of + 5 °C.		
Dimensions	Characteristic	Units	Value
	Length	m	6
	Width	mm	150, 200, 250, 300, 400, 450, 600, 1000
Overall Thickness	3.0 mm		

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of

the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Ensure the surface is dry and free of dust and grease.

APPLICATION

Use Leadax scissors to cut to size and a Leadax roller to mould the product. The temperature needs to be above + 5 °C. Release the liner after after pre-shaping by hand and roller. Any overlap should be 80 mm making sure the area of Leadax Original to be covered is free from dust and grease. Connections should be sealed with Leadax sealant. Remove the protective foil within 30 days.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED
Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Leadax Original Flashing
January 2026, Version 01.01
020945201002246443

LeadaxOriginalFlashing-en-GB-(01-2026)-1-1.pdf

BUILDING TRUST

