

Primer 610 Spray



Revision Date 11.03.2016

Version 1.1

Print Date 05.05.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Primer 610 Spray

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special system

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire AL7 1BQ
United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone number : +44 (0)1707 363899 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol.
Skin irritation, Category 2	H229: Pressurised container: May burst if heated.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H315: Causes skin irritation.
Chronic aquatic toxicity, Category 2	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

Primer 610 Spray



Revision Date 11.03.2016

Version 1.1

Print Date 05.05.2016

H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

- 203-806-2 cyclohexane
- 926-605-8 Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
- 205-500-4 ethyl acetate
- 205-232-8 zinc bis(dibutyldithiocarbamate)

Additional Labelling:

EUH208 Contains zinc bis(dibutyldithiocarbamate). May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
cyclohexane 110-82-7 203-806-2 01-2119463273-41-XXXX	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 STOT SE3; H336	>= 10 - < 20



	Aquatic Acute1; H400 Aquatic Chronic1; H410	
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane 926-605-8 01-2119486291-36-XXXX	Flam. Liq.2; H225 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 10 - < 20
ethyl acetate 141-78-6 205-500-4 01-2119475103-46-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336	>= 5 - < 10
n-hexane 110-54-3 203-777-6	Flam. Liq.2; H225 Repr.2; H361f Asp. Tox.1; H304 STOT RE2; H373 Skin Irrit.2; H315 STOT SE3; H336 Aquatic Chronic2; H411	>= 0,3 - < 1
zinc bis(dibutyldithiocarbamate) 136-23-2 205-232-8 01-2119535161-51-XXXX	Eye Irrit.2; H319 STOT SE3; H335 Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,25 - < 1
Substances with a workplace exposure limit :		
dimethyl ether 115-10-6 204-065-8	Flam. Gas1; H220 Press. Gas	>= 25 - < 50

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.



- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Erythema
Dermatitis
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects

Causes skin irritation.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with



local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force



or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
dimethyl ether	115-10-6	TWA	400 ppm 766 mg/m ³	GB EH40
		STEL	500 ppm 958 mg/m ³	GB EH40
cyclohexane	110-82-7	TWA	100 ppm 350 mg/m ³	GB EH40
		STEL	300 ppm 1.050 mg/m ³	GB EH40
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane		TWA	115 ppm 400 ml/m ³	2000/39/EC
ethyl acetate	141-78-6	TWA	200 ppm	GB EH40
		STEL	400 ppm	GB EH40
n-hexane	110-54-3	TWA	20 ppm 72 mg/m ³	GB EH40

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.



- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor (Type A) and particulate filter
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
P1: Inert material; P2, P3: hazardous substances
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : viscous
- Colour : No data available
- Odour : No information available.
- Odour Threshold : No data available
- Flash point : ca. 20 °C
- Autoignition temperature : No data available
- Lower explosion limit (Vol-%) : 1,2 %(V)
- Upper explosion limit (Vol-%) : 8,3 %(V)
- Flammability : No data available
- Oxidizing properties : No data available

Primer 610 Spray



Revision Date 11.03.2016

Version 1.1

Print Date 05.05.2016

pH	:	Not applicable
Melting point/range / Freezing point	:	No data available
	:	< 35 °C
Vapour pressure	:	Not applicable
Density	:	No data available
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	Not applicable
Relative vapour density	:	No data available
Evaporation rate	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products : No decomposition if stored and applied as directed.



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.#

Components:

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

zinc bis(dibutyldithiocarbamate):

Acute oral toxicity : LD50 Oral: > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.#

Serious eye damage/eye irritation

Not classified based on available information.#

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.#

Respiratory sensitisation: Not classified based on available information.#

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.#

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.#

STOT - repeated exposure

Not classified based on available information.#

Aspiration toxicity

Not classified based on available information.#

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Primer 610 Spray



Revision Date 11.03.2016

Version 1.1

Print Date 05.05.2016

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 3501
14.2 Description of the goods : CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (dimethyl ether)
14.3 Class : 2
Classification Code : 8F
Labels : 2.1
Tunnel restriction code : (B/D)

Primer 610 Spray



Revision Date 11.03.2016

Version 1.1

Print Date 05.05.2016

14.5 Environmentally hazardous : yes

IATA

14.1 UN number : 3501

14.2 Description of the goods : Chemical under pressure, flammable, n.o.s.
(dimethyl ether)

14.3 Class : 2.1

Labels : 2.1

14.5 Environmentally hazardous : yes

IATA_P

14.1 UN number : 3501

14.2 Class : 2.1
Not permitted for transport

IMDG

14.1 UN number : 3501

14.2 Description of the goods : CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.
(dimethyl ether)

14.3 Class : 2.1

Labels : 2.1

EmS Number 1 : F-D

EmS Number 2 : S-U

14.5 Marine pollutant : yes

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted (cyclohexane)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH Information: All substances contained in our Products are
- preregistered or registered by our upstream suppliers, and/or
- preregistered or registered by us, and/or



- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t

VOC-CH (VOCV) : 66,9 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002
Control of Substances Hazardous to Health Regulations 2002
The Management of Health and Safety at Work Regulations 1999
Health and Safety at Work Act 1974
Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Primer 610 Spray



Revision Date 11.03.2016

Version 1.1

Print Date 05.05.2016

Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gases
Flam. Liq.	Flammable liquids
Press. Gas	Gases under pressure
Repr.	Reproductive toxicity
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	Occupational Exposure Limit
PBT	Persistent, bioaccumulative and toxic
PNEC	Predicted no effect concentration
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !