according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikasil® WT-470 (B)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company : Sika Limited

Watchmead

Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom

Telephone : +44 (0)1707 394444

#### 1.4 Emergency telephone number

Emergency telephone num-

: +44 (0)1707 363899 (available during office hours)

ber

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Type of product : Mixture

#### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1

Skin sensitisation, Category 1

H318: Causes serious eye damage.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

posure, Category 3, Respiratory system

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

H335 May cause respiratory irritation.

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)

Precautionary statements

Revision Date 03.02.2016 Version 4.3



Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ va-

pours/ spray.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if

you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Hazardous components which must be listed on the label:

201-083-8 ethyl silicate

• 225-806-1 N-[3-(triethoxysilyl)propyl]ethylenediamine

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### **Hazardous components**

Chemical Name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
ethyl silicate 78-10-4 201-083-8 01-2119496195-28-XXXX	Flam. Liq.3; H226 Acute Tox.4; H332 Eye Irrit.2; H319 STOT SE3; H335	>= 20 - < 25
N-[3-(triethoxysilyl)propyl]ethylenediamine 5089-72-5 225-806-1	Skin Irrit.2; H315 Eye Dam.1; H318 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 5 - < 10
trimethoxyoctylsilane 3069-40-7	Skin Irrit.2; H315	>= 5 - < 10

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)



Revision Date 03.02.2016 Version 4.3 Print Date 13.03.2017

221-338-7 01-2119948401-42-XXXX		
Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dibutylstannane 93925-42-9 300-344-4 01-2119560586-30-XXXX	Flam. Liq.3; H226 Acute Tox.4; H302 Acute Tox.4; H332 Eye Dam.1; H318 Muta.2; H341 Repr.1B; H360FD STOT RE1; H372 Aquatic Chronic3; H412	>= 0,25 - < 0,3

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

Respiratory disorder Allergic reactions Excessive lachrymation


Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)



Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

#### 5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

## 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

## 6.3 Methods and materials for containment and cleaning up


: Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)



## 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling

: Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene

measures when handling chemical products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

## Personal protective equipment

Eye protection : Safety glasses with side-shields

Eye wash bottle with pure water

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)



Revision Date 03.02.2016 Version 4.3 Print Date 13.03.2017

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

**Environmental exposure controls** 

General advice : Do not flush into surface water or sanitary sewer system.

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Appearance : paste

Colour : dark grey

black

Odour : very faint

Odour Threshold : No data available

Flash point : ca. 72 °C

Autoignition temperature : No data available

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Oxidizing properties : No data available

pH : No data available

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)

Revision Date 03.02.2016 Version 4.3 Print Date 13.03.2017

Melting point/range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Vapour pressure : No data available

Density : ca.1,08 g/cm3

at 20 °C

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : ca.250.000 mPa.s

at 20 °C

Viscosity, kinematic : > 20,5 mm2/s

at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

#### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

Hazardous decomposition

products No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)

Revision Date 03.02.2016 Version 4.3



## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

#### **Acute toxicity**

Not classified based on available information.#

## **Components:**

## Silicic acid (H4SiO4), tetraethyl ester, reaction products with bis(acetyloxy)dibutylstannane:

Acute oral toxicity : LD50 Oral (Rat): 1.000 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.#

#### Serious eye damage/eye irritation

Causes serious eye damage.#

## Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.#

Respiratory sensitisation: Not classified based on available information.#

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.#

### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

May cause respiratory irritation.#

## STOT - repeated exposure

Not classified based on available information.#

#### **Aspiration toxicity**

Not classified based on available information.#

### **SECTION 12: Ecological information**

## 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)

Revision Date 03.02.2016 Version 4.3 Print Date 13.03.2017



No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Other adverse effects

No data available

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic

solvents or other dangerous substances

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

## **SECTION 14: Transport information**

**ADR** 

Not dangerous goods

**IATA** 

Not dangerous goods

**IMDG** 

Not dangerous goods

## 14.6 Special precautions for user

No data available

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)

Revision Date 03.02.2016 Version 4.3



Not applicable

### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Prohibition/Restriction**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

of Very High : None of the components are listed

: Not applicable

(=> 0.1 %).

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

REACH Information:

All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

VOC-CH (VOCV) : < 0,01 %

no VOC duties

VOC-EU (solvent) : < 0,01 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002

Control of Substances Hazardous to Health Regulations 2002 The Management of Health and Safety at Work Regulations

1999

Health and Safety at Work Act 1974

Environmental Protection Act 1990 & Subsidiary Regulations

#### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)

Revision Date 03.02.2016 Version 4.3 Print Date 13.03.2017



#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure if

swallowed.

H412 Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Chronic Chronic aquatic toxicity Eye Dam. Chronic aquatic toxicity Serious eye damage

Eye Irrit.

Flam. Liq.

Muta.

Repr.

Skin Irrit.

Skin Sens.

Eye irritation

Flammable liquids

Germ cell mutagenicity

Reproductive toxicity

Skin irritation

Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service DNEL Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

**European Chemicals Agency** 

SVHC Substances of Very High Concern

according to Regulation (EC) No. 1907/2006

## Sikasil® WT-470 (B)



Revision Date 03.02.2016

Version 4.3

Print Date 13.03.2017

vPvB

Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!