

PRODUCT DATA SHEET

Cromar® Patination Oil

Protective film coating for lead work.

PRODUCT DESCRIPTION

Provides a protective film coating for newly installed lead work, especially on pitched roofs. Application prevents unsightly white carbonate staining from building up and spreading to adjacent slates, tiles and masonry. Cromar® Patination Oil enhances the lead colour, relieving the ageing process as the lead develops a natural weathered patina. Treatment is especially important where water flows off the lead onto slate etc. to avoid the white staining which damages the appearance of adjacent materials.

USES

Suitable for external application to lead-work including:

- Flat and pitched lead-work.
- Lead flashings.
- Roof light lead-work.
- Crows Steps.
- Finials.

CHARACTERISTICS / ADVANTAGES

- Brightens and enhances newly installed lead-work.
- Prevents unsightly staining.
- Improves initial appearance and assists in natural ageing of lead.

PRODUCT INFORMATION

Packaging	1 Litre labelled plastic bottles	
Colour	Brown/gold liquid	
Shelf Life	24 months	
Storage Conditions	Store in original packaging in a cool dry place away from ignition sources, out of direct sunlight and protect from frost.	
Density	0.882 g/cm ³	
Flash Point	≥75 °C	
Consumption	50 - 60 m ² / L	
Curing Time	Initial cure	12 hours at +20 °C
	Full cure	Up to 24 hours depending on ambient temperature

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

IMPORTANT! Do not allow Cromar® Patination Oil to come into contact with Bitumen or Polycarbonate sheets.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

The surface must be sound and free of loose or friable materials. To obtain the best result remove all surface dirt, dust and debris arising from installation. Always test a small inconspicuous area prior to full application.

APPLICATION

- Surfaces must be totally dry before application.
- Apply oil evenly using a soft absorbent cloth; work horizontally starting at the top and maintain a wet edge at all times.
- Do not apply in a circular motion as this leave an impression on the lead.
- Only one coat is required.
- Before clipping, apply to underside of lead to approx 50 mm from the edge.
- Apply to all areas, including clips and trim, and coat between laps.
- VERY IMPORTANT – Always apply as soon as possible after installation, or at the end of each working day; if rain is expected, apply before rain.
- Always wear gloves and only apply in a well ventilated area.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® Patination Oil
March 2026, Version 01.01
020945079000247268

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

CromarPatinationOil-en-GB-(03-2026)-1-1.pdf