

# PRODUCT DATA SHEET

## SikaSeal®-147 Decorators Caulk

A HIGHLY FLEXIBLE ACRYLIC SEALANT AND FILLER FOR DECORATORS

### PRODUCT DESCRIPTION

SikaSeal®-147 Decorators Caulk is a highly flexible acrylic sealant and filler for decorators. It is fast drying and can be overpainted within an hour. Suitable for both interior and exterior use.

### USES

- Sealing and filling gaps around windows, doors, skirting boards, cupboards and more.
- Filling cracks in walls and ceilings prior to decorating.

### CHARACTERISTICS / ADVANTAGES

- Superior adhesion to variety of surfaces
- Can be overpainted or covered with wallpaper within an hour
- Suitable for interior and exterior use
- Non-sag with superior flexibility
- Easy to clean up
- Solvent-free

pH	8.5-9.5
Viscosity	250-450,000 cP
Shrinkage	< 25% (ISO10563)

### APPROVALS / STANDARDS

Conforms to ISO11600 F12.5P.

### PRODUCT INFORMATION

<b>Packaging</b>	300ml and 380ml cartridge
<b>Colour</b>	White
<b>Shelf Life</b>	36 months from the date of manufacture if stored correctly.
<b>Storage Conditions</b>	Store in dry conditions, protected from direct sunlight and frost, at temperatures between +5 °C and +25 °C, in undamaged, original, sealed packaging. AVOID FROST.
<b>Density</b>	1.6-1.7 g/cm <sup>3</sup>
<b>Movement Capability</b>	12.5% EN15651-1
<b>Chemical Resistance</b>	Dilute Acids - Fair Dilute Alkaline - Fair Aliphatic Hydrocarbons - Fair AromaticHydrocarbons - Poor
<b>Service Temperature</b>	-15°C to +75°C

### SYSTEM INFORMATION

## Compatibility

Can be used in contact with most building and decorating materials but should not be used against bituminous materials.

## APPLICATION INFORMATION

<b>Sag Flow</b>	No slump ISO7390
<b>Ambient Air Temperature</b>	+4°C to +40°C
<b>Curing Time</b>	3 to 5 days, dependent on thickness, ambient temperature and humidity
<b>Tack Free Time</b>	15 to 60 mins, dependent on thickness, ambient temperature and humidity

## APPLICATION INSTRUCTIONS

The substrate must be clean, dry, sound and homogeneous, free from oils, grease, dust and loose or friable particles. The joint depth must never be greater than the width. In deep sections reduce the depth to approximately 50% of the width with SikaBoom® expanding foam. Apply using standard sealant gun. Cut the tip of cartridge, apply nozzle and cut an angled opening slightly larger than the gap to be filled. Always tool caulk down to ensure a proper bond is achieved.

## LIMITATIONS

Should not be used in conditions of continuous immersion, below ground level, or in areas of high abrasion (e.g. floor joints).

## VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way  
Cross Green Industrial Estate  
Leeds, LS9 0SW  
Tel: 0113 240 3456  
Web: [www.everbuild.co.uk](http://www.everbuild.co.uk)  
Twitter: @everbuild

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



### Product Data Sheet

SikaSeal®-147 Decorators Caulk  
March 2018, Version  
01.01  
020514040000000016  
2/2



SikaSeal-147DecoratorsCaulk-en-GBEVER-(03-2018)-1-1.pdf

BUILDING TRUST

