

PRODUCT DATA SHEET

EVERBUILD® Superlight Wood Filler

2-part, high performance, lightweight wood filler

PRODUCT DESCRIPTION

EVERBUILD® Superlight Wood Filler has been specially developed using lightweight particles to provide a high performance wood filler that is exceptionally easy to sand down and that will accept all types of wood stain, offering a superior level of stainability than heavier particle fillers. The lightweight nature also provides excellent slump resistance in vertical joints and allows deep gaps to be filled in one go. Once mixed the filler sets hard to provide a tough, long-lasting repair to all types of wood, and can be used to any depth.

USES

- Repairing wood damaged by wet rot (in conjunction with EVERBUILD® WET ROT WOOD HARDENER) in both interior and exterior applications.
- General wood filling in windowsills and frames, doors and door frames, banisters, MDF, laminates etc.
- Repair of corner pieces in furniture.
- Repair of wooden constructions.
- Repairing chips and damage in parquet and laminate floors.

CHARACTERISTICS / ADVANTAGES

- 2-part lightweight system – durable, long-lasting and shatterproof.
- Excellent staining characteristics: can be stained, painted, varnished or dyed.
- Suitable for deep vertical applications.
- Chemical cure product – sets within 30 minutes to any depth.
- Sandable in 30 minutes.
- Can be drilled, nailed, planed and carved when dry.
- Flexes with the natural movement of the wood.

Curing System	Chemical reaction
Open Time	10 minutes maximum
Shrinkage	Nil at any depth
Temperature Resistance	-20°C to +100°C.

PRODUCT INFORMATION

Chemical Base	2-part system: Polyester resin and BPO hardener
Packaging	370g and 900g tubs
Appearance / Colour	Lightweight stable paste in light stainable colour
Shelf Life	24 months in original containers at stated storage temperatures.
Storage Conditions	Store upright between 10°C and 25°C in cool, dry conditions away from sources of ignition
Density	Approx 1.0 g/cm ³
Ambient Air Temperature	+5°C to +30°C (optimum 20°C).

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

As the filler may absorb some stains at different rates to the surrounding timber, always test a small area first. Before applying, ensure surfaces are clean, dry, sound and free from dust or any contaminants that may affect adhesion. Lightly sanding the area will improve adhesion. For areas damaged by wet rot, remove as much rotten wood as possible and harden the remaining area with EVERBUILD® WET ROT WOOD HARDENER to give a solid base for filling.

APPLICATION

Mix a golf ball volume of filler (approx 38mm diameter) and a 38mm strip of hardener into a homogeneous paste using the spatula provided. Press firmly into the surface requiring repair, leaving the filler slightly proud of the surface for sanding. Leave to dry for approximately 30 minutes before finishing by sanding/staining etc.

LIMITATIONS

Do not push mixture back into pack once mixed. Avoid contact with skin and eyes. Testing of small area for colour match is recommended. Discard mixed material after 10 minutes if unused. As the manufacturer cannot know all the uses their products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact technical services for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

Product Data Sheet

EVERBUILD® Super-

light Wood Filler

June 2018, Version

01.01

02199010000000092

2 / 2



EVERBUILDSuperlightWoodFiller-en-GBEVER-(06-2018)-1-1.pdf

BUILDING TRUST

