

## PRODUCT DATA SHEET

# Sika® Stabilising Solution

A fine polymer emulsion to bind, seal and strengthen unstable surfaces for overcoating with paint, wallpaper or tiles.

## PRODUCT DESCRIPTION

Sika® Stabilising Solution is a high performance primer. It is formulated with a microscopically fine polymer emulsion enabling it to penetrate deeply into dusty/chalky and badly weathered surfaces to leave a stable sound base for subsequent decoration with paint/wallpaper/tiling etc.

## USES

- Brickwork & Blockwork.
- Stone.
- Render.
- Plaster.
- Existing paint surfaces.
- Pebbledashing/stucco etc.

## CHARACTERISTICS / ADVANTAGES

- Quick drying.
- Ready to use.
- Stabilises and binds interior and exterior friable surfaces prior to overcoating.
- Seal and bonds together chalky, dirty and weathered surfaces.
- Exterior and interior use.

## PRODUCT INFORMATION

Packaging	5 L Jerry Can
Appearance / Colour	Milky white liquid - dries clear
Shelf Life	12 months from date of manufacture when stored according to the manufacturer's instructions.
Storage Conditions	Store in cool, dry conditions, between +5 °C and +25 °C. PROTECT FROM FROST.
Density	1.01 g/cm <sup>3</sup>
pH-Value	7 - 9
Solid Content	11 - 14 %
Viscosity	Approx. 30 cP

## APPLICATION INFORMATION

Consumption	5 - 10 m <sup>2</sup> per litre depending on porosity of surface and method of application.
-------------	---

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LIMITATIONS

- Do not dilute.
- Do not apply externally if rain is imminent (within 6 hours).
- Do not apply below +5 °C.
- Do not allow to enter watercourses.
- Will not restore badly disintegrated render/plaster etc. This will require removing and subsequent re-application.

It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for further advice.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

- Surfaces must be clean, dry (to touch) and free from grease and other contaminants.
- Remove all loose and flaking material with a scraper and a stiff brush back to a sound surface.
- Cure all root causes of penetrating damp and remove all mould contamination with Sika® 404 Fungicidal Wash.

### APPLICATION

- This is a ready to use product. DO NOT DILUTE.
- Stir or shake well before use.
- Apply by brush in a liberal even coat.
- Work from bottom to top to avoid run marks.
- For extremely porous surfaces, apply a second coat when dry.
- Drying time 2-4 hours depending on temperature, humidity etc.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



### Product Data Sheet

Sika® Stabilising Solution  
October 2025, Version 01.01  
021890100000245328

SikaStabilisingSolution-en-GB-(10-2025)-1-1.pdf