

PRODUCT DATA SHEET

S-Scupper V2A/PVC square

PVC plastisol coated stainless steel roof drain/scupper

PRODUCT DESCRIPTION

S-Scupper V2A/PVC square is made of stainless steel (1.4301) completely PVC plastisol coated

USES

Used as a rainwater outlet through the parapet in PVC Sika flat roof systems

CHARACTERISTICS / ADVANTAGES

- Very good resistance to permanent UV exposure
- Roof waterproofing membrane can be hot air welded directly to the base plate
- Outstanding stress-cracking resistance

PRODUCT INFORMATION

Chemical Base	Stainless steel (1.4301) PVC plastisol coated			
Packaging	Depending on the order quantity, the product is packaged on pallets or in cartons			
Colour	Light grey (nearest to RAL 7047)			
Shelf Life	5 years from date of production			
Storage Conditions	The Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C.			
Dimensions	Spigot outside 200 x 100 mm (w x h)	Spigot length 800 mm	Base plate 400 x 200 x 100 mm	Spigot inclination 5°
Thickness	Stainless steel metal 0.8 mm	PVC Plastisol coat ~1.0 mm		

TECHNICAL INFORMATION

Flow rate	35 mm water level 1.95 l/s	45 mm water level 2.90 l/s	75 mm water level 6.20 l/s
Calculated values			

SYSTEM INFORMATION

Compatibility	Compatible with Sikaplan® PVC Roof Waterproofing membranes
----------------------	--

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- The Product may only be used by experienced professionals.
- The Product must not be used in regions with average monthly minimum temperatures lower than -50 °C. Permanent ambient temperature during use must not be higher than +50 °C
- The product must not be altered, cut or adapted.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

APPLICATION

IMPORTANT

Strictly follow installation procedures

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

IMPORTANT

Application by trained personnel

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

INSTALLATION PROCEDURE

Before applying the roof membrane, fasten the Product securely to the roof deck or parapet. For mechanically fastened roofs, design the fasteners to resist the wind load forces at the project location. Reference the current installation instructions for Sika-plan® flat-roof waterproofing membranes.

Reference further documentation where applicable, such as relevant method statements, application manuals and installation or working instructions.

Application below +5 °C

Note: Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

Note: Installation of ancillary products such as contact adhesives or cleaners is limited to temperatures above +5 °C. Refer to the corresponding Product Data Sheets.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
S-Scupper V2A/PVC square
January 2026, Version 01.01
020945012050001002

S-ScupperV2APVCsquare-en-GB-(01-2026)-1-1.pdf

BUILDING TRUST

