

PRODUCT DATA SHEET

SikaSeal® Sanitary Silicone +

A premium quality mid modulus acetoxy cure silicone sealant

PRODUCT DESCRIPTION

SikaSeal® Sanitary Silicone + is an acetoxy cure silicone sealant that cures quickly to provide a permanently flexible, high strength waterproof seal. Specifically designed for sanitary applications and for areas of high humidity. It contains a powerful fungicide to prevent mould growth to the sealant.

USES

- All internal sealing in areas of high humidity or subject to condensation.
- Sealing around baths, showers, basins and sanitary-ware.
- Sealing around work tops and laminates.
- As an adhesive for fixing PVCu trims and panels.

PRODUCT INFORMATION

Packaging	295 mL Cartridge
Colour	White, Translucent, Ivory & Grey.
Shelf Life	24 months from date of manufacture.
Storage Conditions	Store in cool dry conditions between +5 °C and +25 °C.
Density	~1 g/cm ³

TECHNICAL INFORMATION

Shore A Hardness	ca. 20
Tensile Strength	0.4 MPa at break (ISO 8339)
Shrinkage	≤10 % (ISO 10563)
Movement Capability	+/-20 % (ISO 9047)
Service Temperature	-40 °C to +150 °C

CHARACTERISTICS / ADVANTAGES

- Will not discolour on aging even in humid/damp conditions.
- Permanently flexible.
- Quick curing - low dirt pick up.
- Waterproof seal.
- Certified under the harmonized European standard EN 15651 for façade, glazing, cold climate and sanitary applications in compliance with the Construction Product Regulation.

APPROVALS / STANDARDS

Meets ISO 11600 F and G 20LM. EN 15651-1, 2 and 3.

Joint Design	Joint Ratio - Maximum depth 50 % of joint width Minimum Joint Width - 5 mm Maximum Joint Width - 25 mm
Tensile stress at specified elongation	ca. 0.3 MPa at 100 % elongation (ISO 8339)
Elongation at break	>500 % (ISO 37)
Consumption	9 x 9 mm fillet joint at 3.6 linear metres.
Curing Time	3 mm per 24 hours (+23 °C and 50 % RH)
Skin Time / Laying Time	ca. 10 mins at +20 °C
Application condition	+5 °C to +30 °C

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Not for use in conjunction with bitumen or asphalt. Use Weather Mate.
- Not for use on highly porous surfaces such as new concrete or stonework. Priming is advised or use SikaSeal® Construction Silicone.
- Not for use on substrates that may bleed oils, solvent or plasticisers.
- Do not use in the vicinity of, or in conjunction with the edge sealant of double glazed units. Use SikaSeal® Construction Silicone.
- Do not use for perimeter pointing of uPVC. Use LMN Frame Silicone Ultra
- Do not use on soft metals such as lead or brass. Use SikaSeal® Lead.
- Non overpaintable. In applications where overpainting is required, use Weather Mate.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

All surfaces must be clean, dry and dust free. All loose or flaking surface coatings, and old sealant and mastic joints, should be removed before application. Glass, metal and aluminium should be cleaned with a proprietary solvent cleaner prior to application for optimum adhesion. Porous surfaces may require priming - a small area should be tested first.

APPLICATION METHOD / TOOLS

Reference should be made to the recommended joint ratios. If necessary reduce joint depth using Sika Boom® Expanding Foam, or Joint Backer Rod. Furthermore, ensure that the joint design only permits adhesion to two surfaces, as three sided adhesion will impair flexibility.

Cut the tip of the cartridge taking care not to damage the thread. Apply nozzle and cut cleanly at an angle of 45 ° with an opening slightly larger than the gap to be sealed. Apply using a standard sealant gun. Best results will be obtained by keeping an even pressure on the gun trigger and keeping the gun at a constant angle to the surface being sealed.

Smooth down within 10 minutes of application. To ensure a proper bond, always smooth the sealant down using a spatula or piece of wood wetted with a soap and water solution. An improved appearance can be achieved by placing masking tape to both sides of the joint and removing within 5 minutes of application.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
SikaSeal® Sanitary Silicone +
April 2026, Version 01.01
020514030000247746

SikaSealSanitarySilicone+-en-GB-(04-2026)-1-1.pdf