

PRODUCT DATA SHEET

EVERBUILD® EVERFLEX® 700T Silicone Foil Pack

FAST CURE, NEUTRAL CURE SEALANT FOR THE PVCU AND ROOFLINE INDUSTRY

PRODUCT DESCRIPTION

EVERBUILD® EVERFLEX® 700T Silicone Foil Pack is a neutral, alcoxy cure RTV silicone sealant that adheres to a wide range of both porous and non porous surfaces without the need for priming. EVERBUILD® EVERFLEX® 700T Silicone Foil Pack is formulated to a high viscosity to give excellent tooling properties.

USES

- Perimeter pointing internally and externally around PVCu /wood and all other window frames.
- Sealing and as an adhesive onto PVCu, plastic trims and components.
- Suitable as an expansion joint sealant.
- Weather and joint sealing to pre-formed panels.
- Sealing soft metals such as lead, copper and zinc.
- General draught proofing.
- Parapet and roof weather sealing applications.

CHARACTERISTICS / ADVANTAGES

- Excellent adhesion - adheres to most common surfaces including glass, metals, plastics and wood.
- Low dirt pick up - important in PVCu work.
- Good external weathering properties.
- Suitable for use on polycarbonate.
- Foil pack produces less packaging waste than cartridges.

Shrinkage <10 % ISO 10563

Application Temperature +5 °C to + 40 °C

Resistance

Elongation at break >200 % ISO 8339

APPROVALS / STANDARDS

Certified under the harmonized European designated UK standard EN15651 for façade, cold climate and sanitary applications in compliance with the Construction Product Regulation.

PRODUCT INFORMATION

Chemical Base	Neutral cure Silicone
Packaging	600 ml Foil Pack
Colour	Translucent and White
Shelf Life	18 months from date of manufacture Trans 12 months from date of manufacture White
Storage Conditions	Store in original unopened containers between +5 °C and +25 °C
Density	Translucent - 1.0 g/cm ³ White - 1.35 g/cm ³

TECHNICAL INFORMATION

Shore A Hardness	20-30
-------------------------	-------

Movement Capability	±25 % (ISO 9047)
Service Temperature	-50 °C to + 120 °C
Joint Design	Maximum depth 50 % of joint width

APPLICATION INFORMATION

Curing Rate	1 mm per 24 hours
Skin Time	5 - 25 mins

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for advice. Do not use in conjunction with bitumen asphalt, neoprene and certain organic elastomers.

- Do not use in the manufacture of Aquariums, use Aqua Mate Sealant.
- Do not use on substrates that bleed oil, solvents or plasticisers.
- Not overpaintable.
- Staining from plasticiser migration may occur when used on cast, reconstituted or natural stone such as granite, marble or limestone substrates. Customers should test a sample prior to application.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

The surfaces must be clean, dry and free from dust, grease and other contaminants. As quality of plastics can vary, always carry out adhesion tests prior to large scale use.

Improve adhesion by wiping surface with PVCu Solvent Cleaner or white spirits (painted surfaces). Priming is generally not required, although we always advise testing small areas prior to use. Priming on porous substrates use Sikaflex® Primer 3N, non porous use Sika® Aktivator 205.

Joint design should be as follows:

Minimum width: 5 mm. Movement capacity will be impaired if the depth of the joint is greater than the width. For maximum movement accommodation, it is recommended that:

1. The joint depth should be no less than 5 mm.

2. Joint depth should be 5 mm for joints up to 10 mm wide.

3. Joints above 10 mm in width should be half the width in depth up to 20 mm and minimum 10 mm for wider joints.

For deep joints, reduce depth by using Everbuild® Fix and Fill Expanding Foam or a suitable joint backer rod. All joints should be designed so that the seal is placed in a position which does not retain water or form a water trap. Triangular fillets should be no less than 12mm across the face and should be finished with a flat or convex face.

APPLICATION METHOD / TOOLS

Cut the tip of the foil and insert in foil gun. Apply nozzle and cut at an angle of 45 ° with an opening slightly larger than the gap to be sealed. Best results will be obtained by keeping an even pressure on the trigger and keeping the gun at a constant angle to the surface being sealed. To ensure a proper bond, always smooth the sealant down with a spatula or piece of wood. An improved joint appearance can be achieved by placing masking tape to both sides of the joint, removing within 5 minutes of application.

CLEANING OF TOOLS

Uncured sealant - White Spirit or Sika Wonder Wipes.
Cured sealant - Everflex® Silicone Eater.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The

user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

EVERBUILD EVERFLEX700TSiliconeFoilPack-en-GBEVER-(10-2024)-3-2.pdf

Product Data Sheet
EVERBUILD® EVER-
FLEX® 700T Silicone
Foil Pack
October 2024,
Version 03.02
3/3 030000000032



BUILDING TRUST

