

PRODUCT DATA SHEET

Sika® Duct Tape

THE ULTIMATE ALL PURPOSE DUCT TAPE

PRODUCT DESCRIPTION

Sika® Duct Tape is the ultimate all purpose duct tape, made from top quality cloth with an aggressive natural rubber adhesive. It is tough and durable with thousands of uses around the home and industry including jointing PVC sheets, high and low velocity duct work, temporary repairs to pipework etc.

CHARACTERISTICS / ADVANTAGES

- Will stick to most common surfaces including polythene.
- Waterproof.
- Available in a variety of colours.
- Easy tear.
- Tough and durable.

USES

- Jointing PVC sheets, high and low velocity duct work, temporary repairs to pipework and more.

PRODUCT INFORMATION

Chemical Base	Calendered Natural Rubber Adhesive
Packaging	50 mm x 50 m roll
Shelf Life	36 months from date of manufacture.
Storage Conditions	Store in cool dry conditions between +5 and +25 °C. Safe in normal use, however as a precaution keep polythene outer packaging away from children.
Thickness	0.19 mm
Service Temperature	-20 to +80 °C
Adhesion in peel	18 N/25 mm

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

suitability for use. If in doubt contact Technical Services for advice

LIMITATIONS

- Do not use on surfaces that bleed oils or plasticiser.
- It is the user's responsibility to determine

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION METHOD / TOOLS

Ensure surfaces to which tape is to be applied are clean sound and dry. Remove outer packaging from roll of tape. Peel required amount of tape from roll pressing firmly into place while unrolling. Tear off or cut with a knife when finished.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Sika® Duct Tape
September 2026, Version 01.02
02051408000265691

SikaDuctTape-en-GB-(09-2026)-1-2.pdf