

Plumbers Gold Clear

DECLARATION OF PERFORMANCE

No. 98947294

1 UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:

98947294

2 INTENDED USE/S

Sealants for non-structural use in joints in buildings and

pedestrian walkways

Part 1: Sealants for façade; Sealants for exterior and

interior applications

Part 3: Sealants for sanitary joints; Sealing of joints applied

in sanitary areas in the interior of buildings exposed to

non-pressurised water

3 MANUFACTURER: Sika Services AG

Tüffenwies 16 8064 Zürich

4 AUTHORISED REPRESENTATIVE:

Not applicable

5 SYSTEM/S OF AVCP:

System 3

6a DESIGNATED STANDARD:

BS EN 15651-1:2012 and BS EN15651-3:2012

Conformity Assessment body/ies:

2538

Plumbers Gold Clear 98947294 2024/01 , ver. 02 1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Designated Technical Specification
Release of dangerous chemicals	See SDS		
Reaction to fire	NPD		
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10%		
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%		
Tensile properties (ISO8339) for non-structural low modulus sealant used in cold climate	≤0.9 MPa		BS EN 15651- 1:2012
Tensile properties (ISO8340) for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 60%		
Durability	Pass		
Essential Characteristics	Performance	AVCP	Designated Technical
Faceuration Chause standarding	Performance		Specification
Essential Characteristics			
Release of dangerous chemicals	See SDS		<u></u>
Reaction to fire	NPD		<u> </u>
Resistance to flow	≤ 3 mm		DC EN 15651
Loss of volume	≤ 20%		BS EN 15651-
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%		
Microbiological Growth	2		
Durability	Pass		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Paul Thomas

Function: Technical Product

Coordinator

At Leeds on 25 January 2024

Name: Alex West

Function: Product Manager At Leeds on 25 January 2024

End of information as required by UKCA Regulation



Sika Services AG, Zurich, Switzerland

DoP No. 98947294

BS EN 15651-1:2012

Conformity Assessment Body 2538

Sealants for non-structural use in the joints in buildings and pedestrian walkways for Sealants for exterior and interior applications

Release of dangerous chemicals	See SDS
Reaction to fire	NPD
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%
Tensile properties (ISO8339) for non-structural low modulus sealant used in cold climate	≤0.9 MPa
Tensile properties (ISO8340) for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 60%
Durability	Pass

<u>Declarations of Performance Downloads | Sika Limited</u>





21

Everbuild Building Products LTD, Leeds, UK

DoP No. 98947294

EN 15651-3:2012

Conformity Assessment Body 2538

Sealants for non-structural use in the joints in buildings and pedestrian walkways for sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurized water

Release of dangerous chemicals	See SDS
Reaction to fire	NPD
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20%
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%
Microbiological Growth	2
Durability	Pass

for DoP see www.everbuild.co.uk

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

