

PRODUCT DATA SHEET

EVERBUILD® ASBO® Anti-Graffiti Coating

One part, clear coating for protection of surfaces from costly graffiti damage

PRODUCT DESCRIPTION

EVERBUILD® ASBO® Anti-Graffiti Coating is a one-part, silicone based, clear coating for use on porous surfaces, designed to protect against costly damage caused by spray paints, marker pens and fly posting. The repellent coating prevents paint from bonding to the treated surface, allowing easy removal of graffiti using just water and detergent, eliminating the need for harsh chemical cleaners whilst UV stabilisers within the product provide enhanced durability. EVERBUILD® ASBO® Anti-Graffiti Coating is easily applied in one single coat and can be used on concrete, render, masonry, brick, porous stone and previously painted surfaces, leaving a semi-gloss finish where applied.

USES

- Brick
- Stone
- Concrete
- Painted surfaces

CHARACTERISTICS / ADVANTAGES

- Stops paint bonding strongly to the surface, allowing easy removal.
- No harsh cleaning chemicals required.
- Contains UV stabilisers for enhanced durability.
- Can be applied by brush or roller.

PRODUCT INFORMATION

Packaging	5ltr tins
Appearance / Colour	Clear Liquid
Shelf Life	12 months from date of manufacture. Once opened shelf life will be significantly reduced.
Storage Conditions	Store in cool, dry conditions between 5 and 25°C. Keep out of direct sunlight. PROTECT FROM FROST.
Density	0.9 – 0.95 g/cm ³
Consumption	Coverage 3m ² per litre (depending on substrate)

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Areas to be treated must be clean and free from any loose debris. Remove all green growth, mould and fungi contamination from surface with EVERBUILD PATIO WIZARD.

Mask off surrounding areas to protect from splashes etc during application.

APPLICATION

Stir well before use. Apply to surface using a brush or roller ensuring full coverage, including mortar joints on walls. Apply only a thin coat, similar to gloss paint. Take care on textured surfaces where deep depressions may occur. Use a paint brush to remove any excess.

Protect from rain for at least 5-6 hours after application. Allow a minimum 24 hours cure for optimum

performance.

CLEANING OF TOOLS

Clean all tools/equipment immediately after use with EVERBUILD WHITE SPIRIT.

LIMITATIONS

- Do not apply when ambient surface temperature is below 5°C
- Do not apply when rain is imminent or likely within six hours application.
- Not recommended for continuous water immersion.
- Drying times will be significantly extended in cold temperatures.
- EVERBUILD® ASBO® Anti-Graffiti Coating will darken natural stone, concrete and render leaving a semi-gloss finish on all substrates. Always test a small inconspicuous area prior to full application.
- When using a pressure washer keep water jet at least 30cm away from surface and always use a fan tip.
- It is the user's responsibility to determine suitability for use. If in doubt contact technical services for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited