

PRODUCT DATA SHEET

Sika® Anchor-300

anchor fixation through sheet waterproofing membranes

PRODUCT DESCRIPTION

Sika® Anchor-300 is a hard PVC anchor shaft in grey colour combined with Sikaplan® PVC waterproofing membrane flange in yellow colour.

USES

Sika® Anchor-300 is used in double-shell tunnel constructions in combination with waterproofing sheet membranes on base of PVC-p to temporary fix the reinforcement of the inner lining to the outer shell, until the secondary concrete or shotcrete lining is cured and self-supporting.

CHARACTERISTICS / ADVANTAGES

- Allows watertight hot air welded seam with Sikaplan® WP membranes
- Good force transfer through hard PVC shaft
- Waterproofing line around anchor (no additional sealing elements required)
- Anchor steel corrosion-protected
- Quick and simple installation

APPROVALS / STANDARDS

Watertightness test (Vacuum testing):
-0.2 MPa by Sika Testing System TM 87

PRODUCT INFORMATION


Packaging

30 pcs per box

Appearance / Colour

PVC Membrane
PVC Shaft

yellow and black
grey



Shelf Life

5 years shelf life from date of production if stored properly in undamaged, unopened, original sealed packaging

Storage Conditions

Store in dry conditions, protected from direct sunlight, rain, snow and ice,

Product Data Sheet


Sika® Anchor-300

April 2021, Version 01.01

02072080200000014

etc.

Dimensions



Diameter

Shaft: Inside Thread M16, length 200 mm
Membrane: 300 mm

Thickness

Membrane: 2.0 mm

TECHNICAL INFORMATION

Ambient Maximum Temperature of Liquids + 35 °C max

SYSTEM INFORMATION

System Structure

Ancillary products:

- Sikaplan® WP 1100 -types
- Sikaplan® WP 1110 -types
- Sikaplan® WP 1120 -types
- Sikaplan® WP 2101 -types
- Sikaplan® WP 2110 -types
- Sikaplan® WP Protection Sheet-Types
- Sikadur® -31
- Sika® AnchorFix®-2

APPLICATION INFORMATION

Product Data Sheet
Sika® Anchor-300
April 2021, Version 01.01
02072080200000014

BUILDING TRUST



VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Sika® is not responsible for the permissible anchor forces or the related loading calculations.
- Preliminary pull-out tests are mandatory.
- Installation works must only be carried out by Sika® trained contractors.
- The membrane is not UV stabilized and cannot be installed on structures permanently exposed to sunlight and weathering.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The substrate conditions are as defined for the waterproofing membrane system which is to be combined with the Sika® Anchor-300.

APPLICATION METHOD / TOOLS

Installation method:

1. Cut out a small section of the waterproofing system or drill through it directly
2. Drill a hole into the substrate
3. Clean the drill hole with high pressure water jet
4. Clean the drill hole with compressed air
5. Inject Sikadur® -31 or Sika® AnchorFix®-2, or use an-

chor capsule

6. Install Sika® Anchor-300
7. Weld against Sikaplan® PVC membrane
8. Install steel anchor for temporary fixing of rebar cage

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Sika® Anchor-300
April 2021, Version 01.01
020720802000000014

SikaAnchor-300-en-GB-(04-2021)-1-1.pdf