

## PRODUCT DATA SHEET

# Sika® Waterproof & Protector

For long-lasting protection against water ingress and damp

## PRODUCT DESCRIPTION

Sika® Waterproof & Protector is a solvent based treatment that provides long term protection against water and damp. It penetrates deeply into porous surfaces to create a hydrophobic barrier while allowing the surface to breathe.

## USES

- Brickwork.
- Stone & render.
- Masonry.
- Plaster & pebbledash.
- Porous tile grout and pointing.

## CHARACTERISTICS / ADVANTAGES

- Provides long lasting protection against rain, damp and frost.
- Deep penetrating formula for lasting protection.
- Dries clear - colourless.
- Solvent based, quick drying formula.
- Allows the surface to breathe.
- Suitable for brick, stone and screed.
- Suitable for most common mineral surfaces.
- Can be applied by brush, roller or low pressure spray.

## PRODUCT INFORMATION

Packaging	5 L jerry
Appearance / Colour	Clear liquid
Shelf Life	24 months from the date of manufacture (unopened)
Storage Conditions	Store upright between +5 °C and +25 °C. Keep away from heat and ignition sources.
Density	ca. 0.8 g/cm <sup>3</sup>

## APPLICATION INFORMATION

Consumption	Coverage will vary depending on the porosity of the substrate. As a quick guide, brick coverage will be approx. 5 sq. metres per litre for the first coat, 8 sq. metres per litre for the second coat.
-------------	--

## VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## USES

- Do not apply to damp/wet surfaces.
- Do not apply when raining or when rain is imminent.
- Do not use on non porous surfaces.
- Do not use on wood, plastic or rubber.

- Do not use in fishponds.
- Protect windows and surrounding areas from overspray. Remove any overspray immediately whilst the product is still wet, with a cloth
- Note: The surface to be treated may darken after the first application. Always test a small area first PRIOR to coating the whole surface.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

Ensure surface is clean, dry and free from dirt, algae, grease and any loose material.

Treat any organic growth with Sika® Mouldbuster and allow to dry.

Repair cracks or damaged areas before application.

### APPLICATION

Shake container well before use.

Apply by low-pressure spray, brush or roller.

For vertical surfaces: saturate surface from bottom up, then brush over to avoid runs - ensure the entire surface is covered

For horizontal surfaces: flood the entire surface then after 10 minutes, spread the product out with a soft brush, roller or mop to ensure the entire surface is covered .

Apply second coat within 1 hour, while first coat is still wet.

Clean tools with white spirit immediately after use.

Drying time - approx. 1-2 hours, depending on air temperature.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### SIKA LIMITED

Watchmead  
Welwyn Garden City  
Hertfordshire, AL7 1BQ  
Tel: 01707 394444  
Web: [www.sika.co.uk](http://www.sika.co.uk)  
Twitter: @SikaLimited



### Product Data Sheet

Sika® Waterproofer & Protector  
October 2025, Version 01.01  
021890100000245429

SikaWaterprooferProtector-en-GB-(10-2025)-1-1.pdf