

Sikatherm® MW DD

DECLARATION OF PERFORMANCE

No. 15889987

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	15889987
2	INTENDED USE/S	BS EN 13162:2012+A1:2015 Thermal insulation products for buildings. Factory made mineral wool (MW) products.
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	BS EN 13163:2012+A2:2016.
	Notified body/ies:	BSI Assurance UK 0086
7	DECLARED PERFORMANCE/S	

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Length and width	NPD	System 3	BS EN 13163:2012+A2:2016
Thickness	T5	System 3	
Squareness	NPD	System 3	
Flatness	NPD	System 3	
Reaction to Fire	A2-s1, d0	System 1	
Thermal Conductivity - Declared	0.039W/mK	System 3	
Thermal Conductivity - Design	0.039W/mK	System 3	
Thermal Resistance	NPD	System 3	
Compressive Strength at 10% deformation	NPD	System 3	
Compressive Creep	NPD	System 3	
Deformation under specified compressive load and temperature	NPD	System 3	
Dimensional stability	NPD	System 3	
Long-term water absorption by diffusion	NPD	System 3	
Long-term water absorption by immersion	NPD	System 3	
Thickness	NPD	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Dean Grady
Function: Senior Product Engineer
At Preston on 08 November 2022



Name : Gavin White
Function: Head of Product Management
At Preston on 08 November 2022



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sikatherm® MW DD
15889987
2021/10 Version 1



Sika Limited
Watchmead · Welwyn Garden City · Hertfordshire · AL7 1BQ · United Kingdom

DoP No. 15889987

BS EN 13162:2012 +A1 2015

Notified Body 0086

Thermal insulation products for buildings. Factory made mineral wool (MW) products.

Length and width	NPD
Thickness	T5
Squareness	NPD
Flatness	NPD
Reaction to Fire	A2-s1, d0
Thermal Conductivity - Declared	0.039W/mK
Thermal Conductivity - Design	0.039W/mK
Thermal Resistance	NPD
Compressive Strength at 10% deformation	NPD
Compressive Creep	NPD
Deformation under specified compressive load and temperature	NPD
Dimensional stability	NPD
Long-term water absorption by diffusion	NPD
Long-term water absorption by immersion	NPD
Thickness	NPD

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Declaration of Performance

Sikatherm® MW DD

15889987

2021/10 Version 1

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikatherm® MW DD

15889987

2021/10 Version 1