

| Date of last issue: 21.09.2022 | Version 1.3 | Print Date 22.03.2024 |
|--------------------------------|-------------|-----------------------|
| Revision Date: 30.03.2023 | | |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Incorez SLP5016

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Intermediate

1.3 Details of the supplier of the safety data sheet

| Company name of supplier | : | Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ |
|---|---|--|
| Telephone | : | +44 (0)1707 394444 |
| Telefax | : | +44 (0)1707 329129 |
| E-mail address of person responsible for the SDS | : | EHS@uk.sika.com |

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

| Classification (REGULATION (EC) No 1272/2008) | | | | | |
|--|--|--|--|--|--|
| Flammable liquids, Category 3 | H226: Flammable liquid and vapour. | | | | |
| Acute toxicity, Category 4 | H332: Harmful if inhaled. | | | | |
| Respiratory sensitisation, Category 1 | H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. | | | | |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. | | | | |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. | | | | |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

| Date of last issue: 21.09.2022 Revision Date: 30.03.2023 | N | /ersion 1.3 | Print Date 22.03.2024 |
|---|---|--|---|
| Hazard pictograms : | | | |
| Signal word : | Danger | | |
| Hazard statements : | H226 H317 H332 H334 H336 | Flammable liquid and vapour May cause an allergic skin re Harmful if inhaled. May cause allergy or asthma breathing difficulties if inhaled May cause drowsiness or diz | eaction. symptoms or d. |
| Precautionary statements : | Prevention: P210 P261 | Keep away from heat, hot su open flames and other ignitio smoking. Avoid breathing dust/ fume/ g pours/ spray. | n sources. No |
| | P280 | Wear protective gloves/ prote eye protection/ face protectio | |
| | Response: P304 + P340 + P342 + P311 P370 + P378 | P312 IF INHALED: Remove air and keep comfortable for POISON CENTER/ doctor if If experiencing respiratory sy POISON CENTER/ doctor. In case of fire: Use dry sand, | breathing. Call a you feel unwell. mptoms: Call a |
| | | alcohol-resistant foam to exti | nguish. |

Hazardous components which must be listed on the label:

2-methoxy-1-methylethyl acetate 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.





Date of last issue: 21.09.2022 Revision Date: 30.03.2023 Version 1.3

Print Date 22.03.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|--|--|---|--------------------------|
| 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate | Registration number 4098-71-9 223-861-6 01-2119490408-31- XXXX | Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 $_$ specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 % | >= 1 - < 2,5 |
| | | Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 0,031 mg/l | |
| Substances with a workplace expo | sure limit : | | |
| 2-methoxy-1-methylethyl acetate Contains: 2-methoxypropyl acetate <= 1 % | 108-65-6 203-603-9 01-2119475791-29- XXXX | Flam. Liq. 3; H226 STOT SE 3; H336 | >= 25 - < 40 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

| General advice | : Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. |
|----------------|---|
| If inhaled | : Move to fresh air. Consult a physician after significant exposure. |



| Date of last issue: 21.09.2022 Revision Date: 30.03.2023 | | Version 1.3 | Print Date 22.03.202 |
|---|--------|---|----------------------|
| In case of skin contact | : | Take off contaminated clothing and shoes ir Wash off with soap and plenty of water. If symptoms persist, call a physician. | nmediately. |
| In case of eye contact | : | Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. | |
| If swallowed | : | Do not induce vomiting without medical adv Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an uncons | |
| 4.2 Most important symptoms | and e | effects, both acute and delayed | |
| Symptoms | : | Asthmatic appearance Respiratory disorder Allergic reactions Headache Loss of balance Vertigo See Section 11 for more detailed information and symptoms. | n on health effects |
| Risks | : | sensitising effects | |
| | | May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or b ties if inhaled. May cause drowsiness or dizziness. | preathing difficul- |
| 4.3 Indication of any immediat | te med | dical attention and special treatment need | ed |
| Treatment | : | Treat symptomatically. | |

| Extinguishing media | | |
|--------------------------------|---|--|
| Suitable extinguishing media | : | Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical |
| Unsuitable extinguishing media | : | Water |

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known



| Date of last issue: 21.09.2022 Revision Date: 30.03.2023 | | Version 1.3 | Print Date 22.03.2024 |
|---|------|---|-----------------------|
| ucts | | | |
| 5.3 Advice for firefighters | | | |
| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing | j apparatus. |
| Further information | : | Use water spray to cool unopened containers. | |
| | tiv | e equipment and emergency procedures | |
| SECTION 6: Accidental releas | 6e I | neasures | |
| Personal precautions | : | Use personal protective equipment. Remove all sources of ignition. | |
| | | Deny access to unprotected persons. Beware of vapours accumulating to form explosition | ve concentra- |
| | | tions. Vapours can accumulate in low areas. | |
| 6.2 Environmental precautions | | | |
| Environmental precautions | : | Prevent product from entering drains. If the product contaminates rivers and lakes or d respective authorities. | rains inform |

6.3 Methods and material for containment and cleaning up

| Methods for cleaning up | : | Contain spillage, and then collect with non-combustible ab- |
|-------------------------|---|--|
| | | sorbent material, (e.g. sand, earth, diatomaceous earth, ver- |
| | | miculite) and place in container for disposal according to local |
| | | / national regulations (see section 13). |

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| Advice on safe handling | : Avoid formation of aerosol. |
|-------------------------|---|
| | Do not breathe vapours or spray mist. |
| | Avoid exceeding the given occupational exposure limits (see section 8). |
| | Do not get in eyes, on skin, or on clothing. |
| | For personal protection see section 8. |
| | Persons with a history of skin sensitisation problems or asth- |
| | ma, allergies, chronic or recurrent respiratory disease should |
| | not be employed in any process in which this mixture is being |
| | used. |
| | Smoking, eating and drinking should be prohibited in the ap- |



| Date of last issue: 21.09.2022 Revision Date: 30.03.2023 | Version 1.3 | Print Date 22.03.2024 |
|---|--|--|
| | plication area. Take precautionary measures against static dis Provide sufficient air exchange and/or exhaust Open drum carefully as content may be under Take necessary action to avoid static electricity (which might cause ignition of organic vapours) Follow standard hygiene measures when hand products | in work rooms. pressure. / discharge). |
| Advice on protection against : fire and explosion | Use explosion-proof equipment. Keep away fro open flames/ hot surfaces. No smoking. Take p measures against electrostatic discharges. | |
| Hygiene measures : | Handle in accordance with good industrial hygi practice. When using do not eat or drink. Wher smoke. Wash hands before breaks and at the o | n using do not |
| 7.2 Conditions for safe storage, inc | luding any incompatibilities | |
| Requirements for storage : areas and containers | Keep container tightly closed in a dry and well- place. Containers which are opened must be c sealed and kept upright to prevent leakage. Sto ance with local regulations. | arefully re- |
| Further information on stor- : age stability | No decomposition if stored and applied as dire | cted. |

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form | Control parame- | Basis * | | | |
|---------------------------------|--|-------------------------|----------------------|---------------|--|--|--|
| | | of exposure) | ters * | | | | |
| 2-methoxy-1-methylethyl acetate | 108-65-6 | STEL | 100 ppm | 2000/39/EC | | | |
| | | | 550 mg/m3 | | | | |
| | Further inform | nation: Identifies the | possibility of signi | ficant uptake | | | |
| | through the s | kin, Indicative | | - | | | |
| | | TWA | 50 ppm | 2000/39/EC | | | |
| | | | 275 mg/m3 | | | | |
| | | TWA | 50 ppm | GB EH40 | | | |
| | | | 274 mg/m3 | | | | |
| | Further information: Can be absorbed through the skin. The as- | | | | | | |
| | signed substa | ances are those for v | which there are co | ncerns that | | | |
| | dermal absor | ption will lead to syst | temic toxicity. | | | | |
| | | STEL | 100 ppm | GB EH40 | | | |
| | | | 548 mg/m3 | | | | |
| 3-isocyanatomethyl-3,5,5- | 4098-71-9 | TWA | 0,02 mg/m3 | GB EH40 | | | |

Date of last issue: 21.09.2022 Revision Date: 30.03.2023

| trimethylcyclohexyl isocyanate | (NCO) | | | | |
|--------------------------------|---|--|--|--|--|
| | Further information: Substances that can cause occupational | | | | |
| | asthma (also known as asthmagens and respiratory sensitisers) | | | | |
| | can induce a state of specific airway hyper-responsiveness via an | | | | |
| | immunological irritant or other mechanism. Once the airways have | | | | |
| | become hyper-responsive, further exposure to the substance, | | | | |
| | sometimes even in tiny quantities, may cause respiratory symp- | | | | |
| | toms. These symptoms can range in severity from a runny nose to | | | | |
| | asthma. Not all workers who are exposed to a sensitiser will be- | | | | |
| | come hyper-responsive and it is impossible to identify in advance | | | | |
| | those who are likely to become hyper-responsive. Substances | | | | |
| | that can cause occupational asthma should be distinguished from | | | | |
| | substances which may trigger the symptoms of asthma in people | | | | |
| | with pre-existing airway hyper-responsiveness, but which do not | | | | |
| | include the disease themselves. The latter substances are not | | | | |
| | classified as asthmagens or respiratory sensitisers. Further infor- mation can be found in the HSE publication Asthmagen? Critical | | | | |
| | | | | | |
| | assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to sub- | | | | |
| | stances that can cause occupational asthma should be prevented. | | | | |
| | Where this is not possible, the primary aim is to apply adequate | | | | |
| | standards of control to prevent workers from becoming hyper- | | | | |
| | responsive. For substances that can cause occupational asthma, | | | | |
| | COSHH requires that exposure be reduced to as low as is rea- | | | | |
| | sonably practicable. Activities giving rise to short-term peak con- | | | | |
| | centrations should receive particular attention when risk manage- | | | | |
| | ment is being considered. Health surveillance is appropriate for all | | | | |
| | employees exposed or liable to be exposed to a substance which | | | | |
| | may cause occupational asthma and there should be appropriate | | | | |
| | consultation with an occupational health professional over the | | | | |
| | degree of risk and level of surveillance., Capable of causing occu- | | | | |
| | pational asthma., The 'Sen' notation in the list of WELs has been | | | | |
| | assigned only to those substances which may cause occupational | | | | |
| | asthma in the categories shown in Table 1. It should be remem- | | | | |
| | bered that other substances not in these tables may cause occu- | | | | |
| | pational asthma. HSE's asthma web pages | | | | |
| | (www.hse.gov.uk/asthma) provide further information. | | | | |
| | STEL 0,07 mg/m3 GB EH40 | | | | |
| | (NCO) | | | | |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

| Substance name | CAS-No. | Control parame- ters | Sampling time | Basis |
|---|-----------|---|--|-------------|
| 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate | 4098-71-9 | isocyanate- derived diamine (Isocyanates): 1 µmol/mol creati- nine (Urine) | At the end of the period of expo- sure | GB EH40 BAT |



Version 1.3

Print Date 22.03.2024



| Date of last issue: 21.09.2022 | Version 1.3 | Print Date 22.03.2024 |
|--------------------------------|-------------|-----------------------|
| Revision Date: 30.03.2023 | | |

8.2 Exposure controls

| Personal protective equipme | nt | |
|-----------------------------|-----|--|
| Eye/face protection | : | Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. |
| | | Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. |
| Skin and body protection | : | Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work. |
| Respiratory protection | : | In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas. |
| Environmental exposure con | tro | bls |
| General advice | : | Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform |

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties



| Date of last issue: 21.09.2022 Revision Date: 30.03.2023 | | Version 1.3 | Print Date 22.03.2024 |
|---|-----|------------------------------------|-----------------------|
| Physical state Colour | : | liquid colourless, light yellow | |
| Odour | : | solvent-like | |
| Melting point/range / Freezing point | : | No data available | |
| Boiling point/boiling range | : | No data available | |
| Flammability (solid, gas) | : | No data available | |
| Upper/lower flammability or e | ayn | losive limits | |
| Upper explosion limit / Up- per flammability limit | - | | |
| Lower explosion limit / Lower flammability limit | : | 1,5 %(V) | |
| Flash point | : | ca. 54 °C Method: closed cup | |
| Auto-ignition temperature | : | 333 °C | |
| Decomposition temperature | : | No data available | |
| рН | : | Not applicable | |
| Viscosity | | | |
| Viscosity, dynamic | : | ca. 3.700 mPa.s (20 °C) | |
| Viscosity, kinematic | : | > 20,7 mm2/s (40 °C) | |
| Solubility(ies) | | | |
| Water solubility | : | No data available | |
| Partition coefficient: n- octanol/water | : | No data available | |
| Vapour pressure | : | 3,1 hPa | 9/16 |



| Date of last issue: 21.09.2022 Revision Date: 30.03.2023 | Version 1.3 | Print Date 22.03.2024 |
|---|---|-----------------------|
| Density | : ca. 1,04 g/cm3 (20 °C) | |
| Relative vapour density | : No data available | |
| Particle characteristics | : No data available | |
| 9.2 Other information No data available SECTION 10: Stability and re | activity | |
| 10.1 Reactivity No dangerous reaction know 10.2 Chemical stability The product is chemically stability | n under conditions of normal use. ble. | |

10.3 Possibility of hazardous reactions

| Hazardous reactions | : Stable under recommended storage conditions. | |
|----------------------------------|--|--|
| | | Vapours may form explosive mixture with air. |
| 10.4 Conditions to avoid | | |
| Conditions to avoid | : | Heat, flames and sparks. |
| 10.5 Incompatible materials | | |
| Materials to avoid | : | No data available |
| 10.6 Hazardous decomposition pro | bd | licts |

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg



| ision Date: 30.03.2023 | | Version 1.3 | Print Date 22.03.2 |
|---|-------|---|--------------------|
| | | | |
| Acute inhalation toxicity | : | LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist | |
| | | Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method | |
| Acute dermal toxicity | : | LD50 Dermal (Rat): > 7.000 mg/kg | |
| 2-methoxy-1-methylethyl a | ceta | te: | |
| Acute oral toxicity | : | LD50 Oral (Rat): > 5.000 mg/kg | |
| Acute dermal toxicity | : | LD50 Dermal (Rabbit): > 5.000 mg/kg | |
| Skin corrosion/irritation | | | |
| Not classified based on avail | able | information. | |
| Serious eye damage/eye ir | ritat | ion | |
| Not classified based on avail | able | information. | |
| Respiratory or skin sensiti | sati | on | |
| Skin sensitisation | | | |
| May cause an allergic skin re | eacti | on. | |
| Respiratory sensitisation | | antoma or broathing difficultion if inholod | |
| | зуг | nptoms or breathing difficulties if inhaled. | |
| Germ cell mutagenicity Not classified based on avail | able | information | |
| Carcinogenicity | abre | | |
| Not classified based on avail | able | information. | |
| Reproductive toxicity | | | |
| Not classified based on avail | able | information. | |
| STOT - single exposure | | | |
| May cause drowsiness or dia | zzine | ess. | |
| STOT - repeated exposure | | | |
| Not classified based on avail | able | information. | |
| Aspiration toxicity | | | |
| Not classified based on avail | ahle | information. | |



Date of last issue: 21.09.2022 Revision Date: 30.03.2023 Version 1.3

Print Date 22.03.2024

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

: The generation of waste should be avoided or minimized wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Date of last issue: 21.09.2022 Revision Date: 30.03.2023 Version 1.3

Print Date 22.03.2024

SECTION 14: Transport information

| 14.1 UN number or ID number | | | |
|---|---|--|------------------|
| ADR | : | UN 1993 | |
| IMDG | : | UN 1993 | |
| ΙΑΤΑ | : | UN 1993 | |
| 14.2 UN proper shipping name | | | |
| ADR | : | FLAMMABLE LIQUID (2-methoxy-1-methyle | |
| IMDG | : | FLAMMABLE LIQUID (2-methoxy-1-methyle | |
| ΙΑΤΑ | : | Flammable liquid, n.o. (2-methoxy-1-methyle | |
| 14.3 Transport hazard class(es) | | | |
| | | Class | Subsidiary risks |
| ADR | : | 3 | |
| IMDG | : | 3 | |
| ΙΑΤΑ | : | 3 | |
| 14.4 Packing group | | | |
| ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code | • | III F1 30 3 (D/E) | |
| IMDG Packing group Labels EmS Code | : | III 3 F-E, S-E | |
| IATA (Cargo) Packing instruction (cargo aircraft) | : | 366 | |
| Packing instruction (LQ) Packing group Labels | : | Y344 III Flammable Liquids | |
| IATA (Passenger) Packing group Labels | : | III Flammable Liquids | |
| 14.5 Environmental hazards | | | |

14.5 Environmental hazards



| Date of last issue: 21.09.2022 Revision Date: 30.03.2023 | Version 1.3 | Print Date 22.03.2024 |
|---|-------------|-----------------------|
| | | |

ADR

| Environmentally hazardous | : | no |
|---|---|----|
| IMDG Marine pollutant | : | no |
| IATA (Passenger) Environmentally hazardous | : | no |
| IATA (Cargo) Environmentally hazardous | : | no |

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

| UK REACH List of restrictions (Ar | inex 17) | : | Conditions of restriction for the fol- lowing entries should be considered: 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate (Number on list 74) | | |
|--|--|---|--|--|--|
| International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors | | | Not applicable | | |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer | | | Not applicable | | |
| GB Export and import of hazardous chemicals - Prior : Not applicable Informed Consent (PIC) Regulation | | | | | |
| Control of Major Accident Hazards Regulations P5c FLAMMABLE LIQUIDS 2015 (COMAH) | | | | | |
| Volatile organic compounds : | Law on the incentive tax for volatile organic compounds (VOCV) | | | | |
| | Volatile organic compounds (VOC) content: 27,5% w/w | | | | |
| Directive 2010/75/EU of 24 November 2010 on indus emissions (integrated pollution prevention and contro | | | | | |



Date of last issue: 21.09.2022 Version 1.3 Print Date 22.03.2024 Revision Date: 30.03.2023 Volatile organic compounds (VOC) content: 27,5% w/w If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection. Health, safety and environ-: Environmental Protection Act 1990 & Subsidiary Regulations mental regulation/legislation Health and Safety at Work Act 1974 & Subsidiary Regulations specific for the substance or Control of Substances Hazardous to Health Regulations mixture: (COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

Other regulations:

Incorez SLP5016

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

| H226 H315 H317 H319 H330 H334 H335 H336 H411 | | Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Fatal if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. | | | |
|--|---|--|--|--|--|
| Full text of other abbreviations | | | | | |
| Acute Tox. Aquatic Chronic Eye Irrit. Flam. Liq. Resp. Sens. Skin Irrit. Skin Sens. STOT SE 2000/39/EC | : | Acute toxicity Long-term (chronic) aquatic hazard Eye irritation Flammable liquids Respiratory sensitisation Skin irritation Skin sensitisation Specific target organ toxicity - single exposure Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values | | | |
| GB EH40 GB EH40 BAT 2000/39/EC / TWA 2000/39/EC / STEL GB EH40 / TWA GB EH40 / STEL | : | UK. EH40 WEL - Workplace Exposure Limits UK. Biological monitoring guidance values Limit Value - eight hours Short term exposure limit Long-term exposure limit (8-hour TWA reference period) Short-term exposure limit (15-minute reference period) | | | |



| Date of last issue: 21.09.2022 Revision Date: 30.03.2023 | | Version 1.3 | Print Date 22.03.2024 | | | |
|--|--|--|-------------------------|--|--|--|
| ADR CAS DNEL EC50 GHS IATA IMDG LD50 LC50 MARPOL OEL | Dangerou Chemical Derived no Half maxir Globally H Internation Internation Median let once, whic test anima Median let air that kill period) Internation Ships, 197 Occupatio | European Agreement concerning the International Carriage of Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation | | | | |
| PBT PNEC | | Persistent, bioaccumulative and toxic Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency Substances of Very High Concern Very persistent and very bioaccumulative | | | | |
| REACH | : Regulation and of the istration, E | | | | | |
| SVHC vPvB | | | | | | |
| Further information | | | | | | |
| Classification of the mixtur | e: | Classification | n procedure: | | | |
| Flam. Liq. 3 | H226 | Based on proc | duct data or assessment | | | |
| Acute Tox. 4 | H332 | Calculation me | ethod | | | |
| Resp. Sens. 1 | H334 | Calculation me | ethod | | | |
| Skin Sens. 1 | H317 | Calculation me | ethod | | | |
| STOT SE 3 | H336 | Calculation m | ethod | | | |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN