

Date of last issue: 18.01.2024	Version 3.1	Print Date 29.02.2024
Revision Date: 25.01.2024		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name EVERBUILD PINKGRIP BUT ITS WHITE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ
Telephone Telefax	:	+44 (0)1707 394444 +44 (0)1707 329129
E-mail address of person responsible for the SDS	:	EHS@uk.sika.com

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12 Flammable liquids, Category 2	72/2008) H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Date of last issue: 18.01.2024 Revision Date: 25.01.2024		N	/ersion 3.1	Print Date 29.02.2024
Hazard pictograms	:		!	
Signal word	:	Danger		
Hazard statements	:	H225 H319 H336 H412	Highly flammable liquid and v Causes serious eye irritation. May cause drowsiness or diz: Harmful to aquatic life with lor fects.	ziness.
Supplemental Hazard Statements	:	EUH066	Repeated exposure may caus or cracking.	se skin dryness
Precautionary statements	:	Prevention: P210 P233 P261 P273 P280	Keep away from heat, hot sur open flames and other ignition smoking. Keep container tightly closed. Avoid breathing mist or vapou Avoid release to the environm Wear protective gloves/ prote eye protection/ face protection	n sources. No urs. nent. ctive clothing/
		Response: P370 + P378	In case of fire: Use dry sand, alcohol-resistant foam to extir	

Hazardous components which must be listed on the label:

ethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Date of last issue: 18.01.2024 Revision Date: 25.01.2024 Version 3.1

Print Date 29.02.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
ethyl acetate	Registration number 141-78-6 205-500-4 01-2119475103-46- XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Not Assigned 920-750-0 01-2119473851-33- XXXX [corresponding group CAS 64742-49- 0]	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 5 - < 10
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane	Not Assigned 921-024-6 01-2119475514-35- XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 5 - < 10
Titanium dioxide (> 10 μm)	13463-67-7 236-675-5 01-2119489379-17- XXXX		< 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.



ate of last issue: 18.01.2024 evision Date: 25.01.2024		Version 3.1	Print Date 29.02.202
		If symptoms persist, call a physician.	
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious	s person.
.2 Most important symptoms ar	nd e	effects, both acute and delayed	
Symptoms	:	Excessive lachrymation Erythema Loss of balance Vertigo See Section 11 for more detailed information on and symptoms.	health effects
Risks	:	irritant effects	
		Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or	cracking.
.3 Indication of any immediate	mee	May cause drowsiness or dizziness.	cracking.
.3 Indication of any immediate	meo :	May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or	cracking.
•	:	May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or dical attention and special treatment needed Treat symptomatically.	cracking.
Treatment	:	May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or dical attention and special treatment needed Treat symptomatically.	cracking.
Treatment	:	May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or dical attention and special treatment needed Treat symptomatically.	cracking.
Treatment SECTION 5: Firefighting meas	: sur	May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or dical attention and special treatment needed Treat symptomatically. es Alcohol-resistant foam Carbon dioxide (CO2)	cracking.
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing	: sur :	May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or dical attention and special treatment needed Treat symptomatically. es Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water High volume water jet	cracking.
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing media	: sur :	May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or dical attention and special treatment needed Treat symptomatically. es Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water High volume water jet	



Date of last issue: 18.01.2024 Revision Date: 25.01.2024		Version 3.1	Print Date 29.02.2024
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathin	g apparatus.
Further information	:	Use water spray to cool unopened containers.	
SECTION 6: Accidental releas	i ə	neasures	

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions :	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
------------------------	--

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
-------------------------	--



Date of last issue: 18.01.2024 Revision Date: 25.01.2024	Version 3.1	Print Date 29.02.2024
Advice on protection against : fire and explosion	Use explosion-proof equipment. Keep awa open flames/ hot surfaces. No smoking. Ta measures against electrostatic discharges	ake precautionary
Hygiene measures :	Handle in accordance with good industrial practice. When using do not eat or drink. Wash hands before breaks and at	When using do not
7.2 Conditions for safe storage, inc	luding any incompatibilities	
Requirements for storage : areas and containers	Store in cool place. Store in accordance w	ith local regulations.
Further information on stor- : age stability	No decomposition if stored and applied as	directed.
7.3 Specific end use(s)		
Specific use(s) :	Consult most current local Product Data S use.	heet prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m3	2017/164/EU
	Further inforn	nation: Indicative		
		TWA	200 ppm 734 mg/m3	2017/164/EU
		TWA	200 ppm 734 mg/m3	GB EH40
		STEL	400 ppm 1.468 mg/m3	GB EH40
Titanium dioxide (> 10 μm)	13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166



Date of last issue: 18.01.2024 Revision Date: 25.01.2024	Version 3.1 Print Date 29.02.2	
	Eye wash bottle with pure water	
Hand protection	: Chemical-resistant, impervious gloves of proved standard must be worn at all tim chemical products. Reference number f facturer specifications.	nes when handling
	Suitable for short time use or protection Butyl rubber/nitrile rubber gloves (> 0,1 Contaminated gloves should be remove Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	mm)
Skin and body protection	: Protective clothing (e.g. Safety shoes a long-sleeved working clothing, long trou and protective boots are additionaly rec and stirring work.	users). Rubber aprons
Respiratory protection	 In case of inadequate ventilation wear r Respirator selection must be based on exposure levels, the hazards of the proo- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < Ensure adequate ventilation. This can be exhaust extraction or by general ventila ods for determining inhalation exposure ticular to the mixing / stirring area. In can to keep the concentrations under the oc- limits then respiration protection measure 	known or anticipated duct and the safe work- < 10000 ppm be achieved by local ation. (EN 689 - Meth- e). This applies in par- ase this is not sufficent ccupational exposure
Environmental exposure co	ontrols	

General advice	: Prevent product from entering drains.	
	If the product contaminates rivers and lakes or drains inform	1
	respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:liquAppearance:parColour:pin	ste
Odour : hyd	drocarbon-like
Melting point/range / Freezing : No point	o data available



Date of last issue: 18.01.2024 Revision Date: 25.01.2024		Version 3.1	Print Date 29.02.202
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	losive limits	
Upper explosion limit / Up- per flammability limit	:	7,4 %(V)	
Lower explosion limit / Lower flammability limit	:	1,1 %(V)	
Flash point	:	-10 °C Method: closed cup	
Auto-ignition temperature	:	427 °C	
Decomposition temperature	:	No data available	
рН	:	Not applicable	
Viscosity			
Viscosity, dynamic	:	300.000 - 450.000 mPa.s	
Viscosity, kinematic	:	> 30 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	99,9915 hPa	
Density	:	ca. 1,27 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics		No data available	



Date of last issue: 18.01.2024
Revision Date: 25.01.2024

Version 3.1

Print Date 29.02.2024

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous read	tio	ns
Hazardous reactions	:	Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.
10.4 Conditions to avoid		
Conditions to avoid	:	Heat, flames and sparks.
10.5 Incompatible materials		
Materials to avoid	:	No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not classified based on availa	ıble	information.
Components:		
ethyl acetate: Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): ca. 1.600 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg



ate of last issue: 18.01.2024 evision Date: 25.01.2024	Version 3.1	Print Date 29.02.202
Hydrocarbons C7-C9 n-a	kanes, isoalkanes, cyclics:	
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): > 23,3 mg/l Exposure time: 4 h Test atmosphere: vapour	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2.800 mg/kg	
Skin corrosion/irritation		
Repeated exposure may ca	use skin dryness or cracking.	
Serious eye damage/eye i		
Causes serious eye irritation		
Respiratory or skin sensit	sation	
Skin sensitisation		
Not classified based on ava	able information.	
Respiratory sensitisation Not classified based on ava	able information.	
Germ cell mutagenicity Not classified based on ava	able information.	
Carcinogenicity Not classified based on ava	able information.	
Reproductive toxicity Not classified based on ava		
STOT - single exposure		
May cause drowsiness or d	zziness.	
STOT - repeated exposure Not classified based on ava	able information.	
Aspiration toxicity Not classified based on ava	able information.	
1.2 Information on other haza	rds	
Endocrine disrupting prop	erties	
Product:		
Assessment	: The substance/mixture does not contain of ered to have endocrine disrupting propert REACH Article 57(f) or Commission Dele (EU) 2017/2100 or Commission Regulation	ties according to gated regulation

levels of 0.1% or higher.

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at



Date of last issue: 18.01.2024
Revision Date: 25.01.2024

Version 3.1

Print Date 29.02.2024

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

: LL50 (Oncorhynchus mykiss (rainbow trout)): > 13,4 mg/l Exposure time: 96 h

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 12,51 mg/l Exposure time: 96 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of	
mation		unprofessional handling or disposal.	
		Harmful to aquatic life with long lasting effects.	



Date of last issue: 18.01.2024 Revision Date: 25.01.2024 Version 3.1

Print Date 29.02.2024

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number ADR : UN 1133 IMDG : UN 1133 ΙΑΤΑ : UN 1133 14.2 UN proper shipping name ADR : ADHESIVES IMDG : ADHESIVES ΙΑΤΑ : Adhesives 14.3 Transport hazard class(es) Class Subsidiary risks ADR : 3 IMDG 3 : ΙΑΤΑ : 3 14.4 Packing group



Version 3.1	Print Date 29.02.2024
 III F1 3 (E) Exempted according to 2.2.3.1.5 (Viscontion) 	ous substance exemp-
: III : 3 : F-E, S-D : Transport in accordance with 2.3.2.5 of	f the IMDG-Code
: 366 : Y344 : III : Flammable Liquids	
: 355 : Y344 : III	
·	
: no	
: no	
: no	
	 : III : F1 : 3 : (E) : Exempted according to 2.2.3.1.5 (Viscation) : III : 3 : F-E, S-D : Transport in accordance with 2.3.2.5 of : 366 : Y344 : III : Flammable Liquids : 355 : Y344 : III : Flammable Liquids : 355 : Y344 : III : Flammable Liquids : 10 : no : no

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.



Date of last issue: 18.01.2024	Version 3.1	Print Date 29.02.2024
Revision Date: 25.01.2024		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation			:	Not applicable
	The Persistent Organic Pollutants Regulations (retain Regulation (EU) 2019/1021 as amended for Great Bi ain)		:	Not applicable
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors			:	Not applicable
	Regulation (EC) No 1005/2009 on substances that d plete the ozone layer	e-	:	Not applicable
UK REACH List of substances subject to authorisation : Not applicable (Annex XIV)				Not applicable
	(VOCV) Volatile organic co Directive 2010/75/ emissions (integra	mpou EU of	unc f 24 ollu	or volatile organic compounds ds (VOC) content: 29,9% w/w 4 November 2010 on industrial ution prevention and control) ds (VOC) content: 29,9% w/w
	If other regulatory information applies that is not alread Sheet, then it is described in this subsection.	ady pr	rov	ided elsewhere in the Safety Data
	mental regulation/legislation Health and Safety	at Wo	ork	Act 1990 & Subsidiary Regulations Act 1974 & Subsidiary Regulations zardous to Health Regulations

mental regulation/legislation specific for the substance or mixture: Health and Safety at Work Act 1974 & Subsidiary Regulations Control of Substances Hazardous to Health Regulations (COSHH) May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.



Date of last issue: 18.01.2024 Revision Date: 25.01.2024 Version 3.1

Print Date 29.02.2024

SECTION 16: Other information

Full text of H-Statements	
	Lighty flowmobile liquid and yopour
H225 :	Highly flammable liquid and vapour.
H304 : H315 :	May be fatal if swallowed and enters airways. Causes skin irritation.
H319	Causes skin mation. Causes serious eye irritation.
H336 :	May cause drowsiness or dizziness.
H411 :	Toxic to aquatic life with long lasting effects.
Full text of other abbreviations	
Aquatic Chronic :	Long-term (chronic) aquatic hazard
Asp. Tox.	Aspiration hazard
Eye Irrit. :	Eye irritation
Flam. Liq. :	Flammable liquids
Skin Irrit. :	Skin irritation
STOT SE :	Specific target organ toxicity - single exposure
2017/164/EU :	Europe. Commission Directive 2017/164/EU establishing a
	fourth list of indicative occupational exposure limit values
GB EH40 :	UK. EH40 WEL - Workplace Exposure Limits
2017/164/EU / STEL :	Short term exposure limit
2017/164/EU / TWA :	Limit Value - eight hours
GB EH40 / TWA :	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL :	Short-term exposure limit (15-minute reference period)
ADR :	European Agreement concerning the International Carriage of
CA8	Dangerous Goods by Road Chemical Abstracts Service
CAS : DNEL :	Derived no-effect level
EC50 :	Half maximal effective concentration
GHS :	Globally Harmonized System
IATA :	International Air Transport Association
IMDG :	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at
2030	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50 :	Median lethal concentration (concentrations of the chemical in
2000	air that kills 50% of the test animals during the observation
	period)
MARPOL :	International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL :	Occupational Exposure Limit
PBT :	Persistent, bioaccumulative and toxic
PNEC :	Predicted no effect concentration
REACH :	Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC :	Substances of Very High Concern
vPvB :	Very persistent and very bioaccumulative



Date of last issue: 18.01.2024	Version 3.1	Print Date 29.02.2024
Revision Date: 25.01.2024		

Further information

Classification of the mixt	ure:	Classification procedure:
Flam. Liq. 2	H225	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GB / EN