

System Product Data Sheet

Edition 11/12/2014

Identification no:

02 05 08 30 101 0 000001

Sika® ExpansionTape-600

Sika® ExpansionTape-600

Construction**System Description**

The Sika® ExpansionTape-600 is a constant elastic polymer dispersion impregnated PUR sealing tape. It fulfils the requirements of the energy conservation regulations (EnEV) and the RAL instructions.

Uses

Sika® ExpansionTape-600 is used to seal joints between window / door frames and adjacent building components. Sika® ExpansionTape-600 seals against wind, dust, spray water and driving rain.

Characteristics / Advantages

- Open Vapour diffusion structure
- Permanently elastic
- Sound and thermal insulation
- Over paintable with major dispersion paints
- Driving rain tight $\geq 600\text{Pa}$

Tests**Approval / Standards**

Fire resistance class B1 DIN 4102
ift Rosenheim external control
Complies with DIN 18542:2009-07 BG 1
EC-1^{plus}

Product Description

Form Pre-compressed rolls

Colour Black

Packaging See dimensioning

Storage**Storage Conditions / Shelf Life**

24 months from date of production if stored in undamaged, original sealed containers, in dry conditions and protected from direct sunlight and temperatures between -5°C and $+30^{\circ}\text{C}$.

Technical Data

Chemical Base Impregnated PUR soft foam

Classification BG 1

DIN 18542

Joint permeability coefficient	$a \leq 1.0 \text{ m}^3 [\text{h m (daPa)}^{2/3}]$ ift Rosenheim external controlled	DIN EN 1026
Driving rain tightness	> 600 Pa ift Rosenheim external controlled	DIN EN 1027
Diffusion Resistance Coefficient μ	$\mu \leq 100$	DIN EN ISO 12572
Equivalent Air Layer Thickness s_d -Value	$\leq 0.5 \text{ m}$ with 50mm width	DIN EN ISO 12572
Thermal conductivity	$\lambda = 0.052 \text{ W/m K}$	DIN EN 12667
Light and weather resistance	Requirements fulfilled	DIN 18542
Compatibility with adjacent materials	Requirements fulfilled	DIN 18542
Fire Rating	B1	DIN 4102
Temperature stability range	-30°C to +90°C	DIN 18542

System Information

Dimensioning E. g. term 20 / 5-12 stands for:

1st figure: 20 = 20mm width of the tape
2nd figure: 5 - 12 = 5-12 mm =min – max width of joint, =expansion range

Sika® ExpansionTape-600:				
Dimension Joint depth x width	Recommende d joint width	m / Roll	No of rolls per box	Small box
10 / 1-4	1 - 4	13.0	30	390
12 / 2-6	2 - 6	12.0	25	300
15 / 4-9	4 - 9	8.0	20	160
15 / 5-12	5 - 12	5.6	20	112
20 / 6-15	6 - 15	4.3	15	64.5
20 / 9-20	9 - 20	3.3	15	49.5

Other dimensions on request.

Substrate Quality Clean and dry, homogeneous, even, free from grease, dust and loose or friable particles. Paint, laitance and any other contaminants must be removed. Window frame must be clean and free from grease.

Application Conditions / Limitations

Ambient Temperature Between +1°C and +30°C.

Tape Temperature Between +1°C and +30°C.
Warmth accelerates the expansion of the tape; cold temperatures decelerate the expansion of the tape. Best results are achieved if tape is installed with temperatures around 23°C. At 23 °C Sika® ExpansionTape-600 have to be applied within 30 minutes.

Application instructions


Application Method / Tools

After opening the box, open the roll by pulling off the opening / closing tape A. Cut the tape's beginning straight with a scissor.

Remove tape's release liner B and paste the end of the tape on the building component. Align tape to a straight line. Press tape against building component. Avoid stretching of the tape.

The tape should be approx. 10 mm longer than the sealed distance in order to be tight.

Open rolls must be rolled up quickly and tightly and closed with the opening / closing tape A in order to avoid the expansion of the tape.



Fittings and installations:

Before the installation of windows and doors the tape is bonded onto the frame. The tape is installed with an expansion reserve. The tape has to be cut at the frame edges; it must not be installed all round the frame in one piece. The expansion tapes have to be single pieces.

Value Base

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Local Restrictions

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Health and Safety Information

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Legal Notes

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



SIKA LIMITED

Head Office · Watchmead · Welwyn Garden City · Hertfordshire · AL7 1BQ · United Kingdom
Phone: +44 1 707 394444 · Fax: +44 1 707 329129 · www.sika.co.uk

