

PRODUCT DATA SHEET

Cromar[®] Quick Drying Primer

A quick drying bituminous primer.

PRODUCT DESCRIPTION

A low viscosity, high penetration, cold applied, quick drying bituminous solution designed to prime and seal porous roof surfaces prior to the application of bituminous materials.

USES

Quick Drying Bitumen Primer seals porous substrated and promotes the adhesion of bituminous waterproofing systems and sheet coverings. It may be applied to a range of surfaces:

- Concrete.
- Asbestos cement sheeting.
- Metals - mild steel, zinc, lead.
- Slate, lightweight concrete screeds.

PRODUCT INFORMATION

Packaging	Labelled drums and pails dependent on size.
Colour	Black
Shelf Life	18 months
Storage Conditions	Containers must be kept sealed and stored away from sources of heat and ignition.
Dimensions	Available in both 5 Litres and 25 Litres.
Consumption	The Coverage per litre is dependent upon the porosity of the surface: Metal: 6 - 12 m ² /L Concrete: 6 - 8 m ² /L Lightweight concrete screeds and asbestos cement: 3.5 - 5 m ² /L

CHARACTERISTICS / ADVANTAGES

- Fast drying formulation allows rapid over coating and reduced downtime.
- Enhances adhesion of bituminous membranes, coatings, and sealants.
- Suitable for use on porous and non porous substrates.
- Easy to apply.
- Improves overall durability and performance of bituminous systems.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and con-

tains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

Care needs to be taken over preparation of surfaces before application. All surfaces must be free from oil, dirt, dust and loose debris. On metal surfaces all loose rust should be removed using a wire brush and where advanced signs of corrosion are evident the area be treated with a rust inhibitor. Surfaces should be dry for best results, although Bitumen Primer will adhere to damp, but not wet surfaces. Apply using a suitable brush or roller. Bitumen Primer is resistant to rainfall within 20-30 minutes of application.

CLEANING OF TOOLS

Tools may be cleaned with white spirit. Minor spillages should be wiped off surfaces before the compound has set.

Major spillages should be mopped up immediately with an inert, absorbent material, such as sand and disposed of in accordance with regulations.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® Quick Drying Primer
March 2026, Version 01.01
020915797000247180

CromarQuickDryingPrimer-en-GB-(03-2026)-1-1.pdf