

Sarnafil® AT-15

DECLARATION OF PERFORMANCE

No. 64756824

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	64756824
2	INTENDED USE/S	EN 13956:2012 Flexible sheets for waterproofing, plastic and rubber sheets for roof waterproofing
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	2+ and 3
6a	DESIGNATED STANDARD:	EN 13956:2012
	Approved body/ies:	0836 & 2822

Declaration of Performance

Sarnafil® AT-15

64756824

2022.12, ver. 1

22/F6586

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	EN 13956:2012
Watertightness	Pass	System 2+	
Tensile strength Longitudinal (md)1 Transversal (cmd)2	≥ 950 N / 50 mm ≥ 900 N / 50 mm	System 2+	
Elongation Longitudinal (md)1 Transversal (cmd)2	≥ 18 % ≥ 18 %	System 2+	
Root resistance	Pass	System 2+	
Resistance to static loading Soft substrate Rigid substrate	≥ 20 kg ≥ 20 kg	System 2+	
Resistance to impact: Rigid substrate Soft substrate	≥ 1250 mm ≥ 2000 mm	System 2+	
Tear resistance Longitudinal (md)1 Transversal (cmd)	≥ 250 N ≥ 250 N	System 2+	
Joint peel resistance	Failure mode: C, no failure of the joint	System 2+	
Joint shear resistance	≥ 400 N / 50 mm	System 2+	
Durability UV exposure	Pass (> 5'000 h / grade 0)	System 2+	
Foldability at low temperature	≤ -50 °C	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Dean Grady
Function: Senior Product Engineer
At Preston on 09 December 2022



Name : Alex Coward
Function: Head of Technical
At Preston on 09 December 2022



End of information as required by UKCA

Declaration of Performance

Sarnafil® AT-15
64756824
22/12 , ver1.
22/F6586



Sika Limited

Watchmead · Welwyn Garden City · AL7 1BQ · United Kingdom

DoP No. 64756824

EN 13956:2012

Approved Body(ies):

0836 & 2822

Reaction to fire	Class E
Watertightness	Pass
Tensile strength	
Longitudinal (md)1	≥ 950 N / 50 mm
Transversal (cmd)2	≥ 900 N / 50 mm
Elongation	
Longitudinal (md)1	≥ 18 %
Transversal (cmd)2	≥ 18 %
Root resistance	Pass
Resistance to static loading	
Soft substrate	≥ 20 kg
Rigid substrate	≥ 20 kg
Resistance to impact:	
Rigid substrate	≥ 1250 mm
Soft substrate	≥ 2000 mm
Tear resistance	
Longitudinal (md)1	≥ 250 N
Transversal (cmd)	≥ 250 N
Joint peel resistance	Failure mode: C, no failure of the joint
Joint shear resistance	≥ 400 N / 50 mm
Durability	Pass (> 5'000 h
UV exposure	/ grade 0
Foldability at low temperature	≤ -50 °C

Declaration of Performance

Sarnafil® AT-15

64756824

22/12 , ver1.

22/F6586

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

Declaration of Performance

Sarnafil® AT-15
64756824
22/12 , ver1.
22/F6586