

- Fast adhesion, curing and strength build up
- Suitable for bonding and sealing
- **■** Excellent weathering stability
- Very good processing and tooling characteristics

Sikaflex®-268 PowerCure

Sikaflex®-268 PowerCure is an accelerated polyurethane adhesive system suitable for glass and assembly bondig applications where fast curing is required. Sikaflex®-268 PowerCure has outstanding weathering resistance.

For specific applications consult the product data sheet or contact your Sika Technical Service.

PRODUCT BENEFITS

- Curing speed independent of climatic conditions
- PVC and solvent free

AREAS OF APPLICATION

■ Assembly and direct glazing applications



PowerCure Applicator



Typical Product Data	
Chemical base	1-C Polyurethane
Cure mechanism	Moisture curing ^A
Open time	30 minutes approx
Tensile strength (CQP036-1)	6 MPa approx
Elongation at break (CQP036-1)	500% approx
Shelf life (storage below 25°C) (CQP016-1)	9 months for pail

CQP = Corporate Quality Procedure AProvided by PowerCure

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any use.









SIKA LIMITED

Head Office Watchmead Welwyn Garden City Hertfordshire, AL7 1BQ United Kingdom

SIKA IRELAND LIMITED

Sika House Ballymun Industrial Estate Dublin 11 D11 DA2V Ireland

Contact

Phone +441707394444

E-Mail sealingandbondingenquiries@uk.sika.com

www.sika.co.uk/sealantsandadhesives

y @SikaLimited

Contact

Phone +353 1 862 0709 Fax +353 1 862 0707 E-Mail info@ie.sika.com

www.sika.ie

Sikalreland



DD / Industry / Brochines / Sikafley®-268 Downerfure Marine 2nn IIINE 2010