

PRODUCT DATA SHEET

SikaSeal® Flue Jointing Compound

READY MIXED, NON SETTING COMPOUND FOR JOINTING METAL FLUES

PRODUCT DESCRIPTION

SikaSeal® Flue Jointing Compound is a finely dispersed asbestos free material with a stiff consistency. It will not harden completely and small movements can be accommodated without cracking. SikaSeal® Flue Jointing Compound is non-flammable and there is no risk of fire.

CHARACTERISTICS / ADVANTAGES

- Ready mixed formula
- Non setting to accommodate movement
- Temperature resistant up to 200°C
- Internal or external use
- Non flammable

USES

- Jointing metal flues
- Low pressure air ducts
- Chasing pipes through brickwork

PRODUCT INFORMATION

Packaging	500 g and 1 kg tubs
Shelf Life	Up to 12 months when stored according to manufacturers instructions.
Storage Conditions	Store at between +5 °C to +30 °C in original containers. Keep out of direct sunlight.
Density	ca. 1.8 g/cm ³
Service Temperature	-10 °C to +200 °C

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Do not use externally when rain is imminent or on damp surfaces
- Do not alter consistency
- Do not use in excess of +200 °C

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

For maximum adhesion ensure all surfaces are free from all loose dirt and contaminants i.e. rust, soot, dust etc.

APPLICATION

SikaSeal® Flue Jointing Compound should be used straight from the tub. Apply by hand or putty knife working well into the joint to completely fill it. When connecting flue pipes, wrap glass fibre rope around the spigot end before inserting to facilitate a tighter joint.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

SikaSeal® Flue Jointing Compound
September 2026, Version 01.01
020514050000265624

SikaSealFlueJointingCompound-en-GB-(09-2026)-1-1.pdf