

PRODUCT DATA SHEET

Cromar® Drip Trim

Pre-formed GRP Drip Trim

PRODUCT DESCRIPTION

Cromar® Drip Trim in 3 drip depths (60 mm, 90 mm and 141 mm) are made from glass reinforced plastics, offering high strength and excellent long-term durability characteristics, and are designed for use on flat roofing systems.

The Cromar® Drip Trim are designed for use with both the PRO GRP and Flexiglass liquid roof systems. Being an essential component they work together on virtually all types of flat roofs in any domestic and commercial applications, providing perfect all-weather protection.

USES

- Installed along the lowest edge of flat roofs.
- Channels rainwater into the gutter to prevent water ingress.
- Provides a clean, finished edge detail to roof perimeters.
- Protects:
 - Roof decking
 - Fascia boards
 - Walls below from water damage

PRODUCT INFORMATION

Packaging	10 lengths of 3 m banded together.
Colour	Grey
Shelf Life	Shelf life has not been determined due to the longevity of plastic items.
Storage Conditions	The product must be stored undamaged in packaging, in dry conditions at temperatures between + 5 °C and + 30 °C.
Dimensions	60 mm x 90 mm 90 mm x 90 mm 141 mm x 90 mm

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

- Ensure roof deck is:
 - Clean, dry, and level.
 - Fully fixed and structurally sound.
- Check that the edge aligns with the gutter position.
- Install support battens.
- Fix two timber battens around the roof perimeter:
 - Top batten → level with or just below deck.
 - Bottom batten → approx. 10 mm lower than top.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® Drip Trim
July 2026, Version 01.02
020915955000247638

CromarDripTrim-en-GB-(07-2026)-1-2.pdf