
Sikaflex® PRO-3 Purform

DECLARATION OF PERFORMANCE

No. 15886099

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	15886099
2	INTENDED USE/S	EN 14188-2:2004 Cold applied joint sealants intended for use on roads, airfields, bridge decks and parking decks
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN 14188-2:2004

Notified body/ies:

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Bonding strength	NPD	System 4	EN 14188-2:2004
Cohesion	NPD	System 4	
Watertightness	NPD	System 4	
Resistance to deformation:			
Elastic recovery	≥ 70 %	System 4	
Loss of volume	≤ 5 %	System 4	
Durability of watertightness against chemicals	≤ 50 %	System 4	
Durability of cohesion against liquid chemicals	Pass, Class A	System 4	
Durability of all mandated characteristics against ageing	Change of tensile modulus at 100 % extension ≤ ±20 %	System 4	
Resistance to flame	NPD	System 4	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
 Function: Corporate Standardization and Approvals
 At Warsaw on 17 July 2020

Name : Tatiana Ageyeva
 Function: Standardization and Approvals
 At Warsaw on 17 July 2020




End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sikaflex® PRO-3 Purform	EN 15651-4:2012	33809346

Declaration of Performance
 Sikaflex® PRO-3 Purform
 15886099
 2020.07 , ver. 1
 1003, 1009

Template for translation. Only for internal use





20

Sika Services AG, Zurich, Switzerland

15886099

EN 14188-2:2004

Cold applied joint sealants intended for use on roads, airfields, bridge decks and parking decks

Resistance to deformation:

Loss of volume	≤5 %
Elastic recovery	≥ 70 %
Durability of watertightness against chemicals	≤ 50 %
Durability of cohesion against liquid chemicals	Pass, Class A
Durability of all mandated characteristics against ageing	Change of tensile modulus at 100 % extension ≤ ±20 %

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikaflex® PRO-3 Purform
15886099
2020.07 , ver. 1
1003, 1009

Template for translation. Only for
internal use

Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
Sikaflex® PRO-3 Purform
15886099
2020.07 , ver. 1
1003, 1009

4/4

Template for translation. Only for
internal use

BUILDING TRUST

