

Sikalastic®-701

DECLARATION OF PERFORMANCE No. 67409260

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	67409260
2	INTENDED USE/S	ETA-20/1013 / EAD 030350- 00-0402 Liquid-applied roof waterproofing using kits based on polyurethane
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6b	EUROPEAN ASSESSMENT DOCUMENT:	European Assessment document (EAD) no. EAD 030350-00-0402 for Liquid applied roof waterproofing kits
	European Technical Assessment:	ETA-20/1013 of 2020/12/20
	Technical Assessment Body:	ETA-Danmark A/S
	Notified body/ies:	

7 DECLARED PERFORMANCE/S

The SikaRoof PUR-18 kit consists of the following components:

- **Sikalastic -701** — a two-part acrylic polyurethane hybrid, UV protective top layer
- Sikalastic -702 — a two-part polyurea waterproofing layer
- Sika Concrete Primer LO — a two-part, low odour primer for concrete substrates
- Sikafloor -161 — a two-part epoxy primer for asphalt substrates
- Sikalastic Metal Primer — a two-part epoxy primer for preparing metal substrates.

7.1 Mechanical resistance and stability (BWR 1)

Not relevant.

7.2 Safety in case of fire (BWR 2)

Characteristic	Method	Classification
External fire performance	DD CEN/TS1187 : 2012 Tests 1 and 4 Classified to EN 13501-5 : 2016	See Annex A
Reaction to fire	EN ISO 11925-2 : 2010 Classified to EN 13501-1 : 2018	See Annex A

7.3 Health, hygiene and the environment (BWR 3)

Characteristic	Method	Category
Resistance to water vapour	EN 1931 : 2000	See Annex A
Watertightness	EOTA TR-003	See Annex A
Resistance to wind loads	EOTA TR-004	See Annex A
Resistance to dynamic indentation	EOTA TR-006	See Annex A
Resistance to static indentation	EOTA TR-007	See Annex A
Resistance to fatigue movements	EOTA TR-008	See Annex A
Effect of low surface temperatures	EOTA TR-006	See Annex A
Extreme low temperatures	EOTA TR-006 EOTA TR-013	See Annex A
Effects of high surface temperature	EOTA TR-007	See Annex A
Resistance to heat ageing	EOTA TR-011 EN ISO 527-4 : 1997 EOTA TR-006 EOTA TR-008	See Annex A
UV radiation in the presence of water	EOTA TR-010 EN ISO 527-4 : 1997 EOTA TR-006	See Annex A
Resistance to water ageing	EOTA TR-012 EOTA TR-004 EOTA TR-007	See Annex A
Root resistance	EN 13948 : 2007	NPD
Content and/or release of dangerous substances ⁽¹⁾	EOTA TR-034	NPD

(1) The manufacturer has made a declaration that the product does not contain any dangerous substances.

Declaration of Performance

Sikalastic®-701
67409260
2021.01 , ver. 01
1148

Template for translation. Only for
internal use

7.4 Safety and accessibility in use (BWR 4)

Characteristic	Method	Category
Resistance to wind loads	EOTA TR-004	See Annex A
Resistance to water ageing	EOTA TR-012 EOTA TR-004	See Annex A
Slipperiness	SS 92 3515	NPD

7.5 Protection against noise (BWR 5)

Not relevant.

7.6 Energy economy and heat retention (BWR 6)

Not relevant.

7.7 Sustainable use of natural resources (BWR 7)

Not relevant.

7.8 Related aspects to serviceability

Characteristic	Method	Category
Comparative testing of dynamic indentation – variation in installation temperature	EN ISO 527-4 : 1997 EOTA TR-006	See Annex A
Effects of day joints	EOTA TR-004	See Annex A

Declaration of Performance

Sikalastic®-701
67409260
2021.01 , ver. 01
1148

3/6

Template for translation. Only for
internal use

ANNEX A CATEGORISATION OF LEVELS OF PERFORMANCE OF SIKAROOF PUR-18

This annex applies to the SikaRoof PUR-18 roof waterproofing kit used to produce the system described in the main body of the European Technical Assessment.

The substrate applicable to this kit are defined in the main body of the European Technical Assessment.

The kit has the following characteristics:

- water vapour resistance factor (μ) — 2962
- water vapour diffusion — equivalent air layer thickness (S_d) — 4.89 m
- resistance to wind loads — >50 kPa
- assembled kit thickness — 2.23 mm.

The categorisation of levels of performance in accordance with EAD 030350- 00-0402 are:

- external fire performance — $B_{ROOF}(t1)^{(1)}$, $B_{ROOF}(t4)^{(1)}$
- reaction to fire — Euroclass E
- categorisation by working life — W2
- categorisation by climatic zones — M and S
- categorisation by imposed loads — P2 to P4
- categorisation by roof slope — S1 to S4
- categorisation by surface temperature
 - lowest — TL4
 - highest — TH4
- statement on dangerous substances — NPD
- root resistance — NPD
- slipperiness — NPD.

(1) The system tested consisted of a 6 mm thick calcium silicate board, a 2.03 mm coat of Sikalastic -702 and a 0.2 mm coat of Sikalastic -701.

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
Function: Corporate Standardization
and Approvals
At Warsaw on 29 January 2021

Name : Tatiana Ageyeva
Function: Standardization and Approvals
At Warsaw on 29 January 2021



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sikalastic®-701
67409260
2021.01 , ver. 01
1148

Template for translation. Only for
internal use



20

Sika Services AG, Zurich, Switzerland

67409260

EAD 030350- 00-0402

Liquid-applied roof waterproofing using kits based on polyurethane

water vapour resistance factor (μ)	2962
water vapour diffusion – equivalent air layer thickness (S_d)	4.89 m
resistance to wind loads	>50 kPa
assembled kit thickness	2.23 mm.
external fire performance	$B_{ROOF}(t1)^{(1)}$, $B_{ROOF}(t4)^{(1)}$
reaction to fire	Euroclass E
categorisation by working life	W2
categorisation by climatic zones	M and S
categorisation by imposed loads	P2 to P4
categorisation by roof slope	S1 to S4
categorisation by surface temperature	lowest — TL4 highest — TH4

dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikalastic®-701
67409260
2021.01 , ver. 01
1148

Template for translation. Only for
internal use

Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
Sikalastic®-701
67409260
2021.01 , ver. 01
1148

6/6

Template for translation. Only for
internal use

BUILDING TRUST

