

# SikaSeal® Fire Guard

## DECLARATION OF PERFORMANCE

### No. 53809844

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	53809844
2	<b>INTENDED USE/S</b>	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	<b>AUTHORISED REPRESENTATIVE:</b>	Not applicable
5	<b>SYSTEM/S OF AVCP:</b>	4, 3 reaction to fire
6a	<b>HARMONISED STANDARD:</b>	EN 15651-1:2012
	Notified body/ies:	0249

#### Declaration of Performance

SikaSeal® Fire Guard

53809844

2026/02 , ver. 01

1213

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Release of dangerous chemicals	See sds	4	EN 15651-1:2012
Reaction to fire	Class E	3	
Resistance to flow	≤ 5 mm	4	
Loss of volume	≤ 45 %	4	
Tensile properties (i.e. elongation): - break at 23°C	≥ 25 %	4	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Simon Austin  
Function: Senior Project Leader R&D  
At Leeds on 10 February 2026

Name : Paul Thomas  
Function: Product Manager  
At Leeds on 10 February 2026

End of information as required by Regulation (EU) No 305/2011





26

Sika Services AG, Zurich, Switzerland

DoP No. 53809844

EN 15651-1:2012

Notified Body 0249

Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements

Release of dangerous chemicals	See sds
Reaction to fire	Class E
Resistance to flow	≤ 5 mm
Loss of volume	≤ 45 %
Tensile properties (i.e. elongation): - break at 23°C	≥ 25 %

[Declarations of Performance Downloads | Sika Limited](#)

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

SikaSeal® Fire Guard  
53809844  
2026/02 , ver. 01  
1213

**Declaration of Performance**

SikaSeal® Fire Guard

53809844

2026/02 , ver. 01

1213

**4/4**

**BUILDING TRUST**

