

SikaCim[®] No Crack Concrete

DECLARATION OF PERFORMANCE

No. 83724780

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	83724780
2	INTENDED USE/S	Polymer fibres for non-structural use in concrete, mortar and grout
3	MANUFACTURER:	Sika Limited Watchmead Welwyn Garden City Hertfordshire AL7 1BQ United Kingdom
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	DESIGNATED STANDARD:	EN 14889-2:2006
	Approved Body:	1136

Declaration of Performance

SikaCim[®] No Crack Concrete

83724780

2022/09, ver. 01

1161

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Tensile properties	416 MPa	System 3	EN 14889-2:2006
Modulus of elasticity	NPD	System 3	
Consistence with			
0.9 kg/m ³ fibres: Vebe time:	6.3 seconds	System 3	
1.0 kg/m ³ fibres: Vebe time:	6.0 seconds		
Effect on strength of concrete	46 cN/tex	System 3	
Release of dangerous substances	NPD	System 3	
Durability	NPD	System 3	
Fibre			
Length	6 mm		
Linear density	2.72 dtex		
Equivalent diameter	19.5 µm		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: technical Product
Coordinator
At Leeds on 26 September 2022

Name : Mariam Maqsood
Function: Product Manager
At Leeds on 26 September 2022



End of information as required by



Sika Limited, Hertfordshire, United Kingdom

DoP No. 83724780

EN 14889-2:2006

Approved Body: 1136

Polymer fibres for non-structural use in concrete, mortar and grout

Tensile properties	416 MPa
Modulus of elasticity	NPD
Consistence with	
0.9 kg/m ³ fibres: Vebe time:	6.3 seconds
1.0 kg/m ³ fibres: Vebe time:	6.0 seconds
Effect on strength of concrete	46 cN/tex
Release of dangerous substances	NPD
Durability	NPD
Fibre	
Length	6 mm
Linear density	2.72 dtex
Equivalent diameter	19.5 µm

[For declarations see www.everbuild.co.uk](http://www.everbuild.co.uk)

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaCim® No Crack Concrete
83724780
2022/09 , ver. 01
1161

Sika Limited

Welwyn Garden City
Hertfordshire AL7 1BQ
United Kingdom
www.sika.co.uk

Declaration of Performance

SikaCim® No Crack Concrete
83724780
2022/09 , ver. 01
1161

