

# Everflex® Contract 125 One Hour Caulk

## DECLARATION OF PERFORMANCE No. 79939212

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	79939212
2	<b>INTENDED USE/S</b>	Sealants for perimeter wall, window and door joints (façade elements) Indoor (Interior) applications
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	<b>AUTHORISED REPRESENTATIVE:</b>	N/A
5	<b>SYSTEM/S OF AVCP:</b>	4, 3 (reaction to fire)
6a	<b>HARMONISED STANDARD:</b>	EN 15651-1: 2012
	Notified body/ies:	0249

### Declaration of Performance

Everflex® Contract 125 One Hour Caulk  
79939212  
2024/01 , ver. 02  
1213

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	3	EN 15651: 2012
Loss of volume*	≤45 %	3	
Resistance to flow	≤5 mm	3	
Adhesion/ cohesion properties after water immersion (23 °C)	≥25 %	3	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas  
Function: Technical Product Coordinator  
At Leeds on 22 January 2024

Name : Alex West  
Function: Product Manager  
At Leeds on 08 February 2024

End of information as required by Regulation (EU) No 305/2011





14

Sika Services AG, Zurich, Switzerland

DoP No. 79939212

EN 15651-1: 2012

Notified Body 0249

Sealants for perimeter wall, window and door joints (façade elements) Indoor (Interior) applications

Reaction to fire	Class E
Loss of volume*	≤45 %
Resistance to flow	≤5 mm
Adhesion/ cohesion properties after water immersion (23 °C)	≥25 %

<http://dop.sika.com>

### ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

### LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### Declaration of Performance

Everflex® Contract 125 One Hour Caulk  
79939212  
2024/01 , ver. 02  
1213



**Declaration of Performance**

Everflex® Contract 125 One Hour Caulk  
79939212  
2024/01 , ver. 02  
1213

