

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Parex® E140 Epoxy Grout Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy-Cementitious system

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited
Watchmead Welwyn Garden City
Hertfordshire. AL7 1BQ
Telephone : +44 (0)1707 394444
Telefax : +44 (0)1707 329129
E-mail address of person : EHS@uk.sika.com
responsible for the SDS

1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)
24 Hour Emergency Telephone Number +44 870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

Hazard pictograms :



Signal word : Danger

Hazard statements :

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P201	Obtain special instructions before use.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P533	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

Amines, polyethylenepoly-, triethylenetetramine fraction
2-piperazin-1-ylethylamine
Phenol, styrenated

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Amines, polyethylenepoly-, triethylenetetramine fraction Contains: 2-(2-aminoethylamino)ethanol <= 0,3 %	90640-67-8 292-588-2 01-2119487919-13-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071EUH071 Acute toxicity estimate Acute oral toxicity: 1.716 mg/kg Acute dermal toxicity: 1.465 mg/kg	>= 40 - < 60
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 1.620 mg/kg Acute inhalation toxicity (dust/mist): 4,178 mg/l	>= 10 - < 20

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

2-piperazin-1-ylethylamine Contains: 2-(2-aminoethylamino)ethanol <= 0,29 %	140-31-8 205-411-0 01-2119471486-30-XXXX	Repr. 2; H361 STOT RE 1; H372 Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Acute toxicity estimate Acute oral toxicity: 1.999 mg/kg Acute dermal toxicity: 866 mg/kg	>= 10 - < 20
2,4,6-tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27-XXXX	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 2,5 - < 3
Phenol, styrenated	61788-44-1 262-975-0 01-2119980970-27-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 2,5 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

- Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Health injuries may be delayed.
corrosive effects
sensitising effects
- May cause an allergic skin reaction.
Causes serious eye damage.
Suspected of damaging fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Standard procedure for chemical fires.
-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed in a dry and well-ventilated

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

areas and containers place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
------------	---------	-------------------------------	----------------------	---------

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
Wear eye/face protection.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : No special measures required.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : clear, light yellow

Odour : amine-like

Melting point/range / Freezing point : No data available

Initial boiling point and boiling range : > 100 °C

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit
per flammability limit : 13,0 %(V)

Lower explosion limit / Lower flammability limit : 1,3 %(V)

Flash point : > 101 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : No data available

Viscosity

Viscosity, dynamic : ca. 30 mPa.s (20 °C)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : soluble

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	0,07 hPa
Density	:	ca. 1,003 g/cm ³ (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

Components:

Amines, polyethylenepoly-, triethylenetetramine fraction:

- Acute oral toxicity : LD50 Oral (Rat): 1.716 mg/kg
Acute toxicity estimate: 1.716 mg/kg
Method: Calculation method
- Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.
- Acute dermal toxicity : LD50 Dermal (Rabbit): 1.465 mg/kg
Acute toxicity estimate: 1.465 mg/kg
Method: Calculation method

benzyl alcohol:

- Acute oral toxicity : LD50 Oral (Rat): 1.620 mg/kg
Acute toxicity estimate: 1.620 mg/kg
Method: Calculation method
- Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Acute toxicity estimate: 4,178 mg/l
Test atmosphere: dust/mist
Method: Calculation method

2-piperazin-1-ylethylamine:

- Acute oral toxicity : LD50 Oral (Rat): > 1.999 mg/kg
Acute toxicity estimate: 1.999 mg/kg
Method: Calculation method
- Acute dermal toxicity : LD50 Dermal (Rabbit): ca. 866 mg/kg
Acute toxicity estimate: 866 mg/kg
Method: Calculation method

2,4,6-tris(dimethylaminomethyl)phenol:

- Acute oral toxicity : LD50 (Rat): > 1.999 mg/kg
Remarks: Harmful if swallowed.
Annex VI - Harmonised
REGULATION (EC) No 1272/2008

Skin corrosion/irritation

Causes severe burns.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species	:	Rabbit
Assessment	:	Corrosive
Method	:	OECD Test Guideline 404
Assessment	:	irritating
Remarks	:	Annex VI - Harmonised REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species	:	Rabbit
Assessment	:	Causes serious eye damage.
Assessment	:	irritating
Remarks	:	Annex VI - Harmonised REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

SECTION 12: Ecological information

12.1 Toxicity

Components:

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

2-piperazin-1-ylethylamine:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 2735
IMDG : UN 2735
IATA : UN 2735

14.2 UN proper shipping name

ADR : AMINES, LIQUID, CORROSIVE, N.O.S.
(Amines, polyethylenepoly-, triethylenetetramine fraction)
IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.
(Amines, polyethylenepoly-, triethylenetetramine fraction)
IATA : Amines, liquid, corrosive, n.o.s.
(Amines, polyethylenepoly-, triethylenetetramine fraction)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 8	
IMDG	: 8	
IATA	: 8	

14.4 Packing group

ADR
Packing group : II
Classification Code : C7

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG

Packing group : II
Labels : 8
EmS Code : F-A, S-B

IATA (Cargo)

Packing instruction (cargo aircraft) : 855
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosive

IATA (Passenger)

Packing instruction (passenger aircraft) : 851
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosive

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 10% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 10% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations
Health and Safety at Work Act 1974 & Subsidiary Regulations
Control of Substances Hazardous to Health Regulations (COSHH)
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H311 : Toxic in contact with skin.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H361 : Suspected of damaging fertility or the unborn child.
H372 : Causes damage to organs through prolonged or repeated exposure.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Repr. : Reproductive toxicity

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex® E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Repr. 2	H361
STOT RE 1	H372
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



Parex[®] E140 Epoxy Grout Part B

Date of last issue: 31.10.2022
Revision Date: 19.06.2023

Version 2.2

Print Date 29.02.2024

GB / EN