

PRODUCT DATA SHEET

Cromar® F 300 Flat Sheet

300 mm flashing sheet.

PRODUCT DESCRIPTION

Cromar® F 300 Flat Sheet is a versatile flat flashing designed to excel in various roofing applications. Primarily used on the weatherboard beneath slates and tiles, this essential component ensures continuous flashing at roof junctions, providing a reliable barrier against the elements. The Cromar® F 300 Flat Sheet is used for safeguarding roof structures and serves a dual purpose as a gutter lining, showcasing its adaptability.

Supplied in 20-metre rolls for efficient and convenient installation. Specifically crafted for non-heat applications, the Cromar® F 300 Flat Sheet combines safety with functionality.

USES

- Can also be used as gutter lining.
- Primarily used on the weatherboard beneath slates and tiles.

CHARACTERISTICS / ADVANTAGES

- Consistent weight and thickness.
- Excellent finish and appearance.
- High strength and flexibility.
- Excellent long-term durability.
- Easy jointing.

PRODUCT INFORMATION

Packaging	Boxed
Colour	Grey
Shelf Life	24 months
Storage Conditions	The packaging must be stored properly in original, unopened and undamaged sealed packaging, in dry conditions at temperatures between +5 °C and +30 °C
Length	20 m
Width	300 mm
Thickness	1.2 mm

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

Flat section for use as continuous flashing under slates at a roof junction. The flashing can also be used as a gutter lining.

The main flat roof laminate should be extended to cover the nailed section of the flat flashing, which is fixed to the decking on the flat roof. It does not need to be extended up the pitched roof section. The pitched roof section should not be fixed but allowed to 'float', thus allowing for expansion movement.

In some circumstances, a thin support sheet of ply under the flat flashing on the pitched section may be appropriate, dependent on the centres of the existing roof rafters.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® F 300 Flat Sheet
March 2026, Version 01.01
020915955000247639

CromarF300FlatSheet-en-GB-(03-2026)-1-1.pdf