

Date of last issue: 07.02.2023	Version 2.2	Print Date 31.03.2023
Revision Date: 31.03.2023		

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikalastic<sup>®</sup> Rapid-721 Thixo

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use	:	Special coating, Sealant/adhesive, Product is not intended for
		consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Limited
		Watchmead Welwyn Garden City
		Hertfordshire. AL7 1BQ
Telephone	:	+44 (0)1707 394444
Telefax	:	+44 (0)1707 329129
E-mail address of person	:	EHS@uk.sika.com
responsible for the SDS		_

#### **1.4 Emergency telephone number**

National Chemical Emergency Centre (NCEC) 24 Hour Emergency Telephone Number +44 870 190 6777

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Skin irritation, Category 2 Skin sensitisation, Category 1 Specific target organ toxicity - single exposure, Category 3, Respiratory system

- H226: Flammable liquid and vapour.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H335: May cause respiratory irritation.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms		
Signal word	: Warning	•
Hazard statements	: H226 H315 H317	Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction.



Date of last issue: 07.02.2023 Revision Date: 31.03.2023	V	ersion 2.2	Print Date 31.03.2023
	H335	May cause respiratory irritation.	
Precautionary statements :	Prevention:		
	P210	Keep away from heat, hot surface open flames and other ignition s smoking.	
	P261	Avoid breathing mist or vapours	
	P264	Wash skin thoroughly after hand	lling.
	P280	Wear protective gloves/ protective eye protection/ face protection.	ve clothing/
	Response:		
	P303 + P361 + F	P353 IF ON SKIN (or hair): Take ately all contaminated clothing. I with water.	
	P370 + P378	In case of fire: Use dry sand, dry alcohol-resistant foam to exting	

#### Hazardous components which must be listed on the label:

2-ethylhexyl acrylate methyl methacrylate Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and 2-[[2-(2-hydroxyethoxy)ethyl](4methylphenyl)amino]-ethanol

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Date of last issue: 07.02.2023 Revision Date: 31.03.2023 Version 2.2

Print Date 31.03.2023

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
O other discussion and a territoria	Registration number		b = 40 + 200
2-ethylhexyl acrylate	103-11-7 203-080-7	Skin Irrit. 2; H315 Skin Sens. 1B; H317	>= 10 - < 20
	01-2119453158-37-	STOT SE 3; H335	
	XXXX	(Respiratory system)	
	~~~~	Aquatic Chronic 3;	
		H412	
methyl methacrylate	80-62-6	Flam. Liq. 2; H225	>= 10 - < 20
	201-297-1	Skin Irrit. 2; H315	
	01-2119452498-28-	Skin Sens. 1; H317	
	XXXX	STOT SE 3; H335	
		(Respiratory system)	
Reaction mass of 2,2'-[(4-	Not Assigned	Acute Tox. 4; H302	>= 0,025 - <
methylphenyl)imino]bisethanol	911-490-9	Skin Irrit. 2; H315	0,25
and 2-[[2-(2-	01-2119979579-10-	Eye Dam. 1; H318	
hydroxyethoxy)ethyl](4-	XXXX	Skin Sens. 1; H317	
methylphenyl)amino]-ethanol		Aquatic Chronic 3;	
		H412	
		Acute toxicity esti-	
		mate	
		Acute oral toxicity:	
		619 mg/kg	

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Remove contact lenses.



Date of last issue: 07.02.2023 Revision Date: 31.03.2023	3 Version 2.2	Print Date 31.03.2023
	Keep eye wide open while rinsing. If eye irritation persists, consult a special	list.
If swallowed	<ul> <li>Do not induce vomiting without medical a Rinse mouth with water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unco</li> </ul>	
4.2 Most important sympto	oms and effects, both acute and delayed	
Symptoms	: Cough Respiratory disorder Allergic reactions Erythema Dermatitis See Section 11 for more detailed informa and symptoms.	ation on health effects
Risks	: irritant effects sensitising effects	
	Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.	
4.3 Indication of any imme	diate medical attention and special treatment ne	eded
Treatment	: Treat symptomatically.	

-	- J		
	Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Sand
	Unsuitable extinguishing media	:	Water High volume water jet
5.2	Special hazards arising from	the	e substance or mixture
	Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire.
	Hazardous combustion prod- ucts	:	No hazardous combustion products are known



Date of last issue: 07.02.2023 Revision Date: 31.03.2023		Version 2.2	Print Date 31.03.2023
5.3 Advice for firefighters Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing	apparatus.
Further information	:	Use water spray to cool unopened containers.	
SECTION 6: Accidental releas	-		
6.1 Personal precautions, protec	tiv	e equipment and emergency procedures	
Personal precautions	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.	

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
	Smoking, eating and drinking should be prohibited in the ap- plication area.
	Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical



Date of last issue: 07.02.2023 Revision Date: 31.03.2023		Version 2.2	Print Date 31.03.2023
		products	
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from open flames/ hot surfaces. No smoking. Take pr measures against electrostatic discharges.	
Hygiene measures	:	Handle in accordance with good industrial hygie practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the er	using do not
7.2 Conditions for safe storage,	inc	uding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ve place. Store in accordance with local regulations	
Further information on stor- age stability	:	No decomposition if stored and applied as direct	led.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet p use.	rior to any

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU
	Further infor	mation: Indicative		
		STEL	100 ppm	2009/161/EU
		STEL	100 ppm 416 mg/m3	GB EH40
		TWA	50 ppm 208 mg/m3	GB EH40

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.



Date of last issue: 07.02.2023 Revision Date: 31.03.2023	Version 2.2	Print Date 31.03.2023
	Suitable for short time use or protection against Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	t splashes:
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to E long-sleeved working clothing, long trousers). F and protective boots are additionaly recommen and stirring work.	Rubber aprons
Respiratory protection :	In case of inadequate ventilation wear respirato Respirator selection must be based on known of exposure levels, the hazards of the product and ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 Ensure adequate ventilation. This can be achie exhaust extraction or by general ventilation. (El ods for determining inhalation exposure). This a ticular to the mixing / stirring area. In case this is to keep the concentrations under the occupatio limits then respiration protection measures must	ppm ved by local N 689 - Meth- applies in par- is not sufficent nal exposure
Environmental exposure contr	ols	
General advice :	Prevent product from entering drains. If the product contaminates rivers and lakes or respective authorities.	drains inform

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state Appearance Colour Odour	:	liquid paste various ester-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	No data available



Date of last issue: 07.02.2023 Revision Date: 31.03.2023		Version 2.2	Print Date 31.03.2023
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	ca. 24 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
pH	:	substance/mixture is non-polar/aprotic	
Viscosity			
Viscosity, dynamic	:	ca. 26.000 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
<b>Solubility(ies)</b> Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	40 hPa	
Density	:	ca. 1,21 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
---------------------	---	----------------------------------------------

Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid



ate of last issue: 07.02.2023 evision Date: 31.03.2023		Version 2.2	Print Date 31.03.202
Conditions to avoid	:	Heat, flames and sparks.	
0.5 Incompatible materials			
Materials to avoid	:	No data available	
0.6 Hazardous decompositio	n proc	ducts	
No decomposition if stored	and a	pplied as directed.	
ECTION 11: Toxicological	infor	mation	
1.1 Information on hazard cla	isses	as defined in Regulation (EC) No 1272/20	08
Acute toxicity Not classified based on ava	ilable	information.	
Components:			
2-ethylhexyl acrylate:			
Acute oral toxicity	:	LD50 Oral (Rat): 4.435 mg/kg	
methyl methacrylate:			
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg	
Acute inhalation toxicity	:	LC50 (Rat): 29,8 mg/l	
		Exposure time: 4 h Test atmosphere: vapour	
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg	
Reaction mass of 2,2'-[(4- methylphenyl)amino]-etha		/lphenyl)imino]bisethanol and 2-[[2-(2-hy	droxyethoxy)ethyl](4-
Acute oral toxicity	:	LD50 Oral (Rat): 619 mg/kg	
		Acute toxicity estimate: 619 mg/kg Method: Calculation method	
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg	
Skin corrosion/irritation			

Not classified based on available information.



Date of last issue: 07.02.2023	
Revision Date: 31.03.2023	

Version 2.2

Print Date 31.03.2023

#### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

### STOT - single exposure

May cause respiratory irritation.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### 11.2 Information on other hazards

#### Endocrine disrupting properties

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

#### 2-ethylhexyl acrylate:

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,3 mg/l Exposure time: 48 h
Toxicity to algae/aquatic	:	ErC50 (Desmodesmus subspicatus (green algae)): 1,71 mg/l



Date of last issue: 07.02.2023 Revision Date: 31.03.2023	Version 2.2	Print Date 31.03.202
plants	Exposure time: 72 h	
<b>methyl methacrylate:</b> Toxicity to fish :	NOEC (Danio rerio (zebra fish)): 9,4 mg/l	
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): 69 mg/l Exposure time: 48 h Method: OECD Test Guideline 202	
	NOEC : 37 mg/l Exposure time: 21 d Method: OECD Test Guideline 202	
Toxicity to daphnia and other : aquatic invertebrates (Chron- ic toxicity)	NOEC: 37 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea)	
<b>12.2 Persistence and degradability</b> No data available		
<b>12.3 Bioaccumulative potential</b> No data available		
<b>12.4 Mobility in soil</b> No data available		
12.5 Results of PBT and vPvB asse	essment	
Product:		
Assessment :	This substance/mixture contains no component to be either persistent, bioaccumulative and tox very persistent and very bioaccumulative (vPvE 0.1% or higher	tic (PBT), or
12.6 Endocrine disrupting properti	es	
Product:		
Assessment :	The substance/mixture does not contain component ered to have endocrine disrupting properties at REACH Article 57(f) or Commission Delegated (EU) 2017/2100 or Commission Regulation (EU levels of 0.1% or higher.	cording to regulation
12.7 Other adverse effects		
<b>Product:</b> Additional ecological infor- : mation	There is no data available for this product.	
Country GB 100000011488		11 / 16



Date of last issue: 07.02.2023 Revision Date: 31.03.2023 Version 2.2

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

D	ro	4	uc	ŧ.
-	ιu	u	uc	ι

:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe
	way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional
	local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

	ADR	:	UN 1263	
	IMDG	:	UN 1263	
	ΙΑΤΑ	:	UN 1263	
14.2	2 UN proper shipping name			
	ADR	:	PAINT RELATED MA	TERIAL
	IMDG	:	PAINT RELATED MA	TERIAL
	ΙΑΤΑ	:	Paint related material	
14.3	B Transport hazard class(es)			
			Class	Subsidiary risks
	ADR	:	3	
	IMDG	:	3	
	ΙΑΤΑ	:	3	
14.4 Packing group				
	ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III F1 30 3 (D/E)	



Date of last issue: 07.02.2023 Revision Date: 31.03.2023		Version 2.2	Print Date 31.03.2023
Remarks	:	Exempted according to 2.2.3.1.5 (Viscous subs tion)	tance exemp-
<b>IMDG</b> Packing group Labels EmS Code Remarks	: :	III 3 F-E, <u>S-E</u> Transport in accordance with 2.3.2.5 of the IMD	0G-Code
<b>IATA (Cargo)</b> Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	366 Y344 III Flammable Liquids	
<b>IATA (Passenger)</b> Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	355 Y344 III Flammable Liquids	
14.5 Environmental hazards			
<b>ADR</b> Environmentally hazardous	:	no	
<b>IMDG</b> Marine pollutant	:	no	
<b>IATA (Passenger)</b> Environmentally hazardous	:	no	
IATA (Cargo) Environmentally hazardous	:	no	
14.6 Special precautions for use	r		

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors



Date of last issue: 07.02.2023 Revision Date: 31.03.2023	Version 2.2	Print Date 31.03.2023			
Regulation (EC) No 1005/2009 c plete the ozone layer	Regulation (EC) No 1005/2009 on substances that de- : Not applicable plete the ozone layer				
GB Export and import of hazardous chemicals - Prior : Not applicable Informed Consent (PIC) Regulation					
Volatile organic compounds :	Law on the incentive tax for volatile organic co (VOCV) Volatile organic compounds (VOC) content: < no VOC duties				
	n industrial l control) 0% w/w				
If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.					
Health, safety and environ- mental regulation/legislation specific for the substance or mixture:	Environmental Protection Act 1990 & Subsidia Health and Safety at Work Act 1974 & Subsidi Control of Substances Hazardous to Health R (COSHH) May be subject to the Control of Major Accide Regulations (COMAH), and amendments.	iary Regulations egulations			

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

Full text of H-Statements					
H225 H302 H315 H317	:	Highly flammable liquid and vapour. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction.			
H318 H335 H412	:	Causes serious eye damage. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.			
Full text of other abbreviations					
Acute Tox. Aquatic Chronic Eye Dam. Flam. Liq. Skin Irrit. Skin Sens. STOT SE 2009/161/EU	:	Acute toxicity Long-term (chronic) aquatic hazard Serious eye damage Flammable liquids Skin irritation Skin sensitisation Specific target organ toxicity - single exposure Europe. COMMISSION DIRECTIVE 2009/161/EU establishing			



ate of last issue: 07.02.2023 evision Date: 31.03.2023		Version 2.2	Print Date 31.03.2023
		a third list of indicative occupational exp implementation of Council Directive 98/ Commission Directive 2000/39/EC	
GB EH40	:	UK. EH40 WEL - Workplace Exposure	Limits
2009/161/EU / TWA	:	Limit Value - eight hours	
2009/161/EU / STEL	•	Short term exposure limit	
GB EH40 / TWA	•	Long-term exposure limit (8-hour TWA	reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute re	
ADR		European Agreement concerning the In	
	-	Dangerous Goods by Road	g
CAS		Chemical Abstracts Service	
DNEL		Derived no-effect level	
EC50	÷	Half maximal effective concentration	
GHS		Globally Harmonized System	
IATA		International Air Transport Association	
IMDG		International Maritime Code for Danger	ous Goods
LD50		Median lethal dosis (the amount of a ma	
		once, which causes the death of 50% (or test animals)	
LC50	•	Median lethal concentration (concentrat	tions of the chemical in
2000		air that kills 50% of the test animals dur period)	
MARPOL		International Convention for the Preven	tion of Pollution from
	•	Ships, 1973 as modified by the Protoco	
OEL		Occupational Exposure Limit	
PBT		Persistent, bioaccumulative and toxic	
PNEC		Predicted no effect concentration	
REACH		Regulation (EC) No 1907/2006 of the E	uropean Parliament
	•	and of the Council of 18 December 200	
		istration, Evaluation, Authorisation and	
		cals (REACH), establishing a European	
SVHC		Substances of Very High Concern	
vPvB	:	Very persistent and very bioaccumulativ	

### Further information

Classification of the	mixture:	Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !



Date of last issue: 07.02.2023 Revision Date: 31.03.2023 Version 2.2

Print Date 31.03.2023

GB / EN