

PRODUCT DATA SHEET

Sarnavap® Tape F

BUTYL RUBBER ADHESIVE TAPE FOR SARNAVAP® VAPOUR CONTROL LAYERS

PRODUCT DESCRIPTION

Sarnavap® Tape F is a butyl rubber, double-sided adhesion sealing tape with a controlled stretch range.

USES

- Taping lap splices in plastic Sarnavap® vapour control layers (polyethylene) based material and for attaching Sarnavap® VCL to smooth surfaces.

CHARACTERISTICS / ADVANTAGES

- Finger-lift release liner
- Controlled adhesive stretch range
- High durability
- Used only at airtight level



PRODUCT INFORMATION

Chemical Base	Adhesive: Butyl rubber Release liner: Polypropylene
Packaging	Refer to current price list
Appearance / Colour	Smooth flat profile. Black
Shelf Life	2 years from date of production
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.
Length	40,00 m (-5 cm / +20 cm)
Width	15 mm (±1,0 mm)
Thickness	1,0 mm (-0 mm / +0,2 mm) Density: 1,2 g/cm ³ (+20 °C)

SYSTEM INFORMATION

System Structure	Compatible system products: <ul style="list-style-type: none">▪ Sarnavap® PE vapour control layer
Compatibility	Not compatible in direct contact with PVC, tar, asphalt, hot bitumen, wood preservatives with surfactants and substances containing oil, solvents or wetting agents. These materials could adversely affect the product properties.

APPLICATION INFORMATION

Ambient Air Temperature	Condition tape in application environment temperature before applying. For seams and detailing min. + 5° C / max. + 40° C
Substrate Temperature	+ 5° C / max. + 40° C

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surfaces must be dry, clean and free from dust, grease and other materials which could affect adhesion.

SUBSTRATE PREPARATION

All dust and loose particles must be completely removed from all surfaces before application of tape.

APPLICATION METHOD / TOOLS

Reference must be made to further documentation where applicable, such as relevant method statement, application manual and installation or working instructions.

Overlaps

Adjoining sheets must overlap 80 mm.

FURTHER DOCUMENTS

- Installation instructions: Sarnafil® and Sikaplan® flat roof systems

LIMITATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- The use of Sarnavap® Tape F is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.
- Do not use if exposed to permanent UV

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data


Sheet for the product concerned, copies of which will be supplied on request.

TECHNICAL ENQUIRIES

Tel: 01707 358500
Web: www.sarnafil.co.uk
Twitter: @SikaSarnafilUK

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Sarnavap® Tape F
September 2018, Version 01.01
020945051200000002

SarnavapTapeF-en-GBSARNA-(09-2018)-1-1.pdf