

PRODUCT DATA SHEET

Cromar[®] Over Fascia Vent

Over fascia ventilator to aid airflow.

PRODUCT DESCRIPTION

Over fascia vents establish clear airflow into the cavity between the fascia board and the felt; this makes it a great choice for situations like re-roofing or a new build.

USES

- Provides continuous roofline ventilation for cold or warm roof constructions.
- Reduces condensation in roof voids and attic spaces.
- Helps maintain the longevity of roofing materials by allowing airflow.
- Suitable for pitched roofs with standard fascia boards.
- Can be used in conjunction with ridge vents or eaves ventilation systems.

CHARACTERISTICS / ADVANTAGES

- Durable, weather-resistant construction.
- Easy to install along fascia boards.
- Designed to prevent ingress of birds and pests.
- Lightweight and low-maintenance.
- Promotes effective airflow to prevent moisture build-up.
- UV-stable for long-term outdoor performance.

PRODUCT INFORMATION

Packaging	Cardboard box containing 50 vents.
Shelf Life	As a plastic item there is no specific shelf life.
Storage Conditions	Store laid flat in a cool dry place, away from direct sunlight.
Dimensions	1 m x 25 mm x 35 mm 1 m x 38 mm x 48.5 mm

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable condi-

tions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

The over fascia ventilator should be positioned directly on top of the fascia board, with the stop section flush against the vertical edge of the fascia board. It should be nailed down, through the anchor holes provided, across the entire length of the eaves. This product can be used with all tiles and can be used in other roofing details.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet

Cromar® Over Fascia Vent
February 2026, Version 01.01
020945201000246895

CromarOverFasciaVent-en-GB-(02-2026)-1-1.pdf