

Sika MonoTop®-4100 Protect

DECLARATION OF PERFORMANCE

No. 67274749

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	67274749
2	INTENDED USE/S	EN 1504-3:2005 Structural and non-structural repair products for concrete for use in buildings and civil engineering works
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ System 3 for reaction to fire
6a	HARMONISED STANDARD:	EN 1504-3:2005
-	Notified body/ies:	0099, 0370

67274749 2025.07, ver. 1 1124

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification	
Compressive strength	≥ 45 MPa	System 2+		
Chloride ion content	≤ 0.05 %	System 2+	<u> </u>	
Adhesive bond	≥ 2.0 MPa	System 2+		
Restrained shrinkage/expansion	≥ 2.0 MPa	Pa System 2+		
Carbonation resistance	Pass $(d_k \le control concrete (MC(0,45))$	System 2+		
Elastic modulus	≥ 20 GPa	System 2+	EN 1504- 3:2005	
Thermal compatibility	NPD	System 2+		
Skid resistance	NPD	System 2+		
Coefficient of thermal expansion	NPD	System 2+		
Capillary absorption	NPD	System 2+		
Reaction to fire	A1	System 3		
Dangerous substances	NPD	System 2+		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Rob Doherty Function: Head Of Product Management – Engineered

Refurbishment

At Welwyn Garden City on 30 July

2025

Name: Steve Holmes

Function: Senior Technical Manager At Welwyn Garden City on 30 July 2025

Delmes

End of information as required by Regulation (EU) No 305/2011





10

67274749

Sika Services AG, Zurich, Switzerland

EN 1504-3:2005

Notified Bodies 0099, 0370

Structural and non-structural repair products for concrete for use in buildings and civil engineering works

Compressive strength \geq 45 MPa
Chloride ion content \leq 0.05 %
Adhesive bond \geq 2.0 MPa
Restrained shrinkage/expansion \geq 2.0 MPa

Carbonation resistance Pass $(d_k \le control concrete (MC(0,45))$

Elastic modulus ≥ 20 GPa
Reaction to fire A1

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland www.sika.com

Declaration of Performance

Sika MonoTop®-4100 Protect 67274749 2025.07, ver. 1 1124

