

PRODUCT DATA SHEET

SikaForce®-300 Primer

Adhesion promoter for SikaForce® plastic repair adhesives

TYPICAL PRODUCT DATA (FURTHER VALUES SEE SAFETY DATA SHEET)

Chemical base	Solvent-based adhesion promoter
Colour (CQP001-1)	Colorless, clear
Application temperature	15 – 30 °C
Application method	Spray
Consumption	depending on substrate porosity 20 ml/m ²
Flash-off time	minimum 5 minutes maximum 2 hours
Shelf life	36 months ^A

CQP = Corporate Quality Procedure

^{A)} stored in sealed container in up-right position in a dry place at ≤ 25 °C

DESCRIPTION

SikaForce®-300 Primer is a solvent-based colourless adhesion promoter. SikaForce®-300 Primer is specifically formulated for the treatment of bond faces prior to the application of SikaForce®-301 and SikaForce®-302 plastic repair adhesives. This primer provides good adhesion without previous activation steps on many substrates.

Product Benefits

- Easy spray application
- Fast drying
- Enhanced adhesion on a wide variety of plastic substrates

AREAS OF APPLICATION

SikaForce®-300 Primer is used to improve adhesion on a broad range of different plastic substrates.

Seek manufacturer's advice and perform tests on original substrates before using SikaForce®-300 Primer on materials prone to stress cracking.

This product is suitable for experienced professional users only. Tests with actual substrates and conditions have to be performed ensuring adhesion and material compatibility.

METHOD OF APPLICATION

Primer Preparation

Surfaces must be clean, dry and free from grease, oil, dust and contaminants.

Application

SikaForce®-300 Primer has to be processed between 15 °C and 30 °C (product, ambient, and substrate temperature).

SikaForce®-300 Primer has to be applied in a thin and even coat to the surface in short bursts to avoid dripping or running of the primer.

If pre-treated area is not bonded within the maximum flash-off time, the pre-treatment process has to be repeated (once only). Consumption and method of application depends on the specific nature of the substrates.

IMPORTANT NOTE

SikaForce®-300 Primer contains solvent which may dull the surface finish of some freshly applied paints. Preliminary trials must be carried out.

Never apply to porous substrates since it may not dry completely and might influence adhesion or the properties of the adhesive.

Protect adjacent surfaces by masking where necessary.

SikaForce®-300 Primer must not be used for tooling/smoothing or as cleaning agent.

FURTHER INFORMATION

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Industry.

Copies of the following publications are available on request:

- Safety Data Sheets

PACKAGING INFORMATION

Aerosol can	200 ml
-------------	--------

BASIS OF PRODUCT DATA

All technical data stated in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

HEALTH AND SAFETY INFORMATION

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

DISCLAIMER

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PRODUCT DATA SHEET

SikaForce®-300 Primer
Version 01.01 (02 - 2024), en_GB
014761000013002000

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

