

PRODUCT DATA SHEET

Cromar[®] Metal-Kote[®] Goosewing Grey

An oil-based, waterproof roof coating designed for protecting and re-coating metal roofs, including corroded surfaces.

PRODUCT DESCRIPTION

Designed for coated and uncoated metal roofs such as steel, galvanised steel, aluminium, cast iron, copper, tin, lead, stainless steel, corrugated sheets and standing seam systems. Provides a waterproof seal and is suitable for use over surface rust without priming.

USES

- Waterproofing and refurbishment of deteriorated or corroded metal roofs.
- Overcoating plastic-coated metal roofing panels, particularly where corrosion enters via unprotected edges.
- Suitable for industrial, commercial, agricultural, domestic and local authority buildings.

CHARACTERISTICS / ADVANTAGES

- Single-coat system – no primer required, even over rust.
- Direct application onto surface rust with a watertight seal that inhibits further rust spread.
- High adhesion even without priming.
- Suitable for endlaps and overlaps.

PRODUCT INFORMATION

Packaging	20 L pails
Colour	Grey
Shelf Life	12 months
Storage Conditions	Store between + 5 °C and + 25 °C, away from direct sunlight and heat sources.
Density	~1.36 g/cm ³
Flash Point	+40 °C
Volatile organic compound (VOC) content	20 % w/w
Viscosity	> 20.5 mm ² /s (+40 °C)
Application condition	Application temperature range: + 5 °C to + 25 °C, avoiding conditions within 3°C of the dew point.

VALUE BASE

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

Not suitable for bituminous or asphalt-coated surfaces.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

- Apply by brush or heavy-duty sprayer; ensure even application, particularly on corrugated sheeting.
- Do not thin: mix thoroughly before use.
- Surface preparation:
 - Power wash metal surfaces before coating.
 - Remove loose rust, debris, or poorly adhered existing coatings.
 - Tighten or replace loose fixings.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited



Product Data Sheet
Cromar® Metal-Kote® Goosewing Grey
March 2026, Version 01.01
020915909000247447

CromarMetal-KoteGoosewingGrey-en-GB-(03-2026)-1-1.pdf